

POS-L156 Windows Android 15.1/15.6 POS MSR

(M/N:POS- L 15 6)

□□□

□□□□□□□□□□ I3 I5 □□□□□□□□  
 □□□□ Msata SSD 64GB □ SSD 128GB □ 256 GB □□□□□  
 58mm □ 80mm □□□□□□□□□□□□  
 □□□□□□□□□□  
 □□□□ MSR □ VFD220 □□□□□□□□□□  
 □□□□□□□□□□

□□

□□	POS- L 156
□□	15.6□□□□□□□□□□ POS□□
□□	□□□□□□□□
□□	□□□□□□□□ □□
□□	
□□□□	15.6□□□□□□□□□□
□□□□	1366*768
□□	25 0cd/m <sup>2</sup>
□□□□□□□□	□□□□1 60 □□□□1 50
□□□□	□□ □□G+G □□□□
□□□□	15.6□□□□□□□□ /□□□□ □□□□□□□□□□1366*768□□
□□□□	2*20 VFD □□□□□□□□□□
□□	
□□	Intel Celeron Bay Trail J1900 2.0GHz □ Intel Celeron J4125 □ Intel Core I3 / I 5 CPU □□
□□□□	1*SO-DIMM DDRIII□□□□□□ 4GB DDR3L/ 1333 MHZ□□□□□□ 8GB □ □
□□□□	Msata SSD 64GB □□□□□□□□ 256GB
□□□□	□□ Real Tek ALC662□□□□□□
□□□□	10/100Mbs □ Realtek RTL8111F □□□□□□ □□ Mini PCI-E□□□□□□□□□□□□□□ WIF□□
□□□□	Windows 7/8/10 □ □□□□ WEPOS, Linux
□□□□	
□□□□ □□□□□□ J1900	□□□□*1 □□□□12V DC *1 LAN □ RJ-45*1 □□□□□ RJ11 USB*6 15PIN D-sub VGA *1 RS 232*1 □□□□*1 □□□□□□□□*1
□□	
80mm□□□□□□	□□□□□□□□ 1 5 0mm/s □□□□□□ 79.5-/+ 0.5mm □□□□□□□□□□□□ 72mm □□□□□□□□□□□□□□□□□□□□ 50km

58mm	
	85mm/s
	57.5-/+ 0.5mm 48mm
	50km
MSR	MSR
	4ohm/5w
	6.5 15.6 8.0 15.6
	490 * 310 * 48 5
	110-240V /50-60HZ DC12/5A W/o W/ 58mm DC12V/7A W/ 80mm























