

POS-M1162A/W Android WindowsPOS

(M/N:POS- M1162 -W/POS- M1162 -A)

□□□

□□□□□□□□ I3 I5 □ RK3288 CPU □□
 □□□□ Msata SSD 64GB □SSD 128GB □ 256 GB □□
 80mm □□□□□□□□
 □□□□□□□□□□
 VFD220 □□□□□□□□□□
 NFC □□□□□□□□□□
 □□□□□□□□□□

□□

□□	POS- M1162 -W	POS- M1162 -A
□□	11.6□□□□Windows □□□POS □□	11.6 □□□□□□ □□□pos□□
□□	□□□□□□□□	
□□	□□□□□□	
□□		
□□□□	11.6□□IPS □□□□□□	11.6□□IPS □□□□□□
□□□	1366*768 , 1920*1080 □□	1366*768 , 1920*1080 □□
□□	2 30 0cd/m	
□□□□□□	□□□□1 60 □□□□1 50	
□□□	□□ □□G+G □□□□	
□□	4.3□□□□□□□□□□800*480□□	
□□□□	2*20 VFD □□□□□□□□□□	
□□		
□□	Intel Celeron Bay Trail J 4125 2.0GHz , Intel core I3/I5 □□	ARM Cortex-A17 -RK 3288 □ □ 1.8GHz CPU
□□□□	1*SO-DIMM DDR IV□□□□2133 Mhz 2GB/4GB 8GB □□	□□ 2GB DDRIII
□□□□	Msata SSD 64GB □□□□□□ 256GB	16 GB eMMC□□□□32 GB TF□□ □□□□
□□□	□□Real Tek ALC662□□□□	□□Real Tek□□□□ALC5640
□□□	10/100Mbs□Realtek RTL8111F □□□□□□ □□Mini PCI-E□□□□□□□□WIFI□ □	10M/100M RTL8201F,10M/100M/1000M RTL8211E□□
□□□□	Windows 7/8/10□ □□ □□WEPOS,Linux	□□ 7.1□□□ 8.1
□□□		

I/O (J 4125 /RK3288)	*1	
	12V DC *1	
	RS232 * 1	
	RJ-45*1	
	USB * 5	
	RJ11 *1	
	VGA(15Pin D-sub)*1	TF*1 SIM*1
	MIC *1 *1	RJ11*1
80mm		
200/		
79.5-/+ 0.5mm 72mm		
100km		
	8ohm/3W	
	IEEE 802.11 a/b/g/n	
	3G/4G	
NFC	ISO14443A	
	/	
	5.0MP/1D/2D	
	6000mAh	
3.1 3.8		
	180 * 370 * 380	
21	370*365*392/12kg	
0 40		
	- 10 60	
	10%~80%	
	10%~90%	
110-240V /50-60HZ AC DC12/ 7 A		
	/ /	
FCC A /CE /LVD/CCC		





















11.6 inch Touch Screen Computer System
Model: POS-M1162
Configuration: I3800+GEMM+MSTW+RTC+Display
8200 Printer+2D Scanner
Power Input: DC 12V/1A
CE FC
1909M11622118200001
Made in China



11.6 inch Touch Screen Computer System
Model: POS-M1162
Configuration: i1900+GBRAM+4SSD+NFC+Display
80MM Printer+2D Scanner
Power Input: DC 12V 7A
POS#1162213820001
Made in China
CE FC

