

POS-M680 nfc 58mm pos

□□

□□□	corte-a8, 1.0ghz
□□□□	android 4.0
□□	512M RAM+4G □
sd	□□ sd□□□□ tf 32GB)
□□	7□□□□□□□□□□1024 * 600 □□□□□
□□□	□□□□□□□□□□
□□□	□□□□□□□□□□□□:57 mm, □□: 42MM
□□□□□	ISO7811 1/2/3 □□, □□□□□
ic □□□□	ISO7816 □□
rfid □□□	ISO14443TypeA□TypeB □ ISO15693
□□	3□□□□□□□□□□
□□□□□	1□/2 d □□□□□□□□□□□□□□□□
communication	gsm:850/900/1800/1900, wcdma□B1/B2/B5,CDMA: BC0
□□□□	802.11b/g/□/n □□□□□□, □□□□□
□□	□□□□□□□□□□□□□□□□□□□□
□	2 * □□□
psam □□□	3 * sam □ slot,ISO7816 □□
sim □□□	1 * sim □□□
□□	□□□□□1000□□, 7.4v
usb	2 * USB2.0, 1 * □□ usb □□ otg □□
□□□	1 * RJ45 □
hdmi	1 * hdmi □□
□	2 * RJ11 □□
RS232	1 * rs232
□□	dc 9 v/3 a
□□□□	□□□□:-20 °C ~ 60 °C □□□□:-30 °C ~ 70 °C □□□□: 10%~90%
□□	240 (l) x 220 (w) x 80 mm (h)
□□	1.2 □□
□□□□	350 (l) * 260 (w) * 150 (h) mm
□□□□	2.5 □□