

1. 0.1 Android

OCpC- 001 -W/ OCPC- 001 -

OCOM 001 Window Android VESA

- 1.
2. 64 ,SSD 12 8 d 256 n
- 3.

	OCPC- 001- W	OCPC- 001 -
	10.1	10.1
	10.1	10.1
	1280* 800	1280* 800
	25 0cd/	
a	1 60 ; 1 50	
s	GG	
	J1 9 00 2.0GHz	Rockchip RK3288 1.8G ,A63 CPU
	1*SO-D DDRIII 1333*/1600 4	2 DDRIII
	Msata 64	16 eMMC
	Real Tek ALC662	Real Tek ALC5640
	10/100 Mbs, Realtek RTL8111F	WIFI/802.11/b/g/n
	Windows 2010 7 8 WEPOS, Linux	Android 8.1 A63 Android 7.1
/O (J1900)	p *1 , 12V DC *1 RJ-45*1 RS232*1 USB *4 *1	
/O (RK3288)	p * 1 12V DC *1 RJ-45*1 HDMI*1 USB * 2 SIM*1 SD*1 *1	
/O (A63)	p * 1 12V DC *1 RJ-45*1 USB * 4 SD*1 *1	

□□	
□□	□ 1.5 □□ □□ 3.0 □□
□□□□□□	3 60* 290* 180 mm
□□	
□□□□	0 □ 40 □□□
□□□□	- 10 □ 60 □□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12 V /5A □□
□□□	□□□□/□□/□□□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC













