

POS 终端 产品 介绍 资料

POS-T2)



□□

□□	- T2
□□	5.5英寸 触摸屏 分辨率
□□	3.8 英寸 / 64 00英寸
□□□□	□□□100-240V , 50/60Hz ,1.5A □□□ 5 V □□ /2 A
□□□□	USB C □
□□	5.5英寸 触摸屏 □□
□□	720*1280 IpS
□□	
□□□□	□□MT6797 Tri-Cluste-A72*2A53*8 2.3GHz□□
□□	3 □□
□□	16GB□□
□□	2G/3G/ 4G
□□□□	□□ 8.0
□□	□□□□□□□□ .□□□□
□□	□□4.0
□□□□	WIFI 802.11 bgnac
□□□□	58mm □□□□ □□□ □□□
□□	□□□58mm□□□□≤40mm
□□□□	5□□□ □□□□ , 2D □□□□□□□□
□□□□	□□□ISO/IEC 14443A&B□Mifare□felica□
SIM□□	Sim*2□□□□□□Sim*1Sam*1□□□□
□□□	□□□□□□□□
□□ p □□	□□□□□/STQC □□ p □□ □□□□□
GPS □ AGPS	□□GPSAGPS
□□□□□	□□
□□□□	
□□	USB C □*1
□□	□□ □□□*1
□□□□	□□□□*1
□□	
□□□□	0 □ 40 □□□
□□□□	- 10 □ 60 □□□
□□□□	10%~80%
□□□□	10%~90%