

OCBS-LA11

OCBS-LA11

Wavelength	650-670nm
Power	100 mW
Beam Diameter	2.5 mm @ 600mm @ 100mm UPC / EAN
Beam Quality	M ²
Spot Size	0.10mm @ 4mil @ PCS 0.9
Beam Divergence	30mrad @ 650nm
Beam Stability	3000000:1
Beam Encodings	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5 ...
Interface	
Interface	PS2 RS232 USB
Voltage	DC +5 V + / -5V
Current	100 mA
Power Consumption	<40 W
Interface	RS232
Beam Angle	45° 60°
Dimensions	L165mm X W63mm X H87mm
Weight	129g
Material	
Operating Temperature	0°C 40°C
Storage Temperature	-40°C 60°C
Humidity	5-95% RH
ESD Protection	±15KV ±8KV
Shock Resistance	1.5g
EMI / RFI	FCC Class A CE
Regulatory	CDRH 21 CFR

OCBS-LA11

