

58 POS Android

OCPP -58E

OCPP -58E
OCPP -58E

;

paperroll;

GB18030 uncommoncharacters

;

LOGO;

Windows Linux Android IOS

ApplicationArea



OCP-58E





OCPP-58E





OCPP-58E



□□

□□	□□
----	----

□□□□	□□□□	□□
	□□□□	48MM
	□□□	384dots / □□□8dots / □□□203DPI□
	□□□□	90□□/□
	□□□□	USB□USB +□□
	□□□	3.75□□□□□□□□□□□□□□
	□□	□□A□32□□□□/□ □□B□42□□□□/□ □□□□□□□□16□
	□□	□□GB18030□□/□□□□□□
	□□□□	ANKcharacter□□□A.□1.5×3.0□□□12×24dots□ □□B.□1.1×2.1□□□9×17dots□ □□/□□□□□3.0×3.0mm□24×24□□
□□□□□	□□□□□	PC437 / □□□/ PC850 / PC860 / PC863 / PC865 / WestEurope / □□/□□□□□/□□□□/ □□/ WPC1252 / PC866 / PC852 / PC858 / IranII / □□□□□/□□□□□/ PT151,1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 / □□□□□□□□□□PC1001□□PT151,1251□/ □□WPC1257□□□□PC864□□□□□□□□□□
	□□	UPC-A / UPC-E / JAN13□□EAN13□□/ JAN8□□EAN8□□CODE39 / ITF / CODABAR / CODE93 / CODE128
□□□□	□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60mm
	□□□□	□□□Clameshell□□□□
□□□□	□□	ESC / POS
□□	□□□□□	□□□AC 100V-240V□50-60Hz □□□DC 12V / 2A
	Casher□□□□	DC 12V / 1A
□□	□□□□□	4K
	NV Flash	40K
□□□□	□□	590□
	□□	185 * 130 * 112□MM□
□□	□□	□□□5~45°C□ □□□10~80□
	□□	□□□-10~50°C □□□□10~90□□□□□□□□
□□□□□	□□□□□□	50KM□□□□□□≤12.5□