

OCBS-W011

RF 433MHZ

- 1 RF 433MHZ
- 2 100
- 3
- 4
- 5

OCBS-W011

OCBS-W011	
Wavelength	650-670nm
Power	200mW
Beam Diameter	2.5~600mm 100 UPC / EAN
Beam Quality	PCS 0.9 0.10mm 4mil
Beam Divergence	30 @ 650nm
Beam Color	Red
Beam Modulation	UPC / EAN 128 ASCII codabar 2 of 5 2 of 5 93 MSI 11 ATA RSS
Frequency	433MHz
Frequency Stability	433MHz 300 15
Battery Capacity	900mAh 3.3V
Battery Life	100h
Current Consumption	< 40mA
Interface	USB
Operating Temperature	45 60
Dimensions	L165mm X W63mm X H87mm
Weight	129g
Material	Plastic
Color	Red
Power Output	0~40mW
Operating Temperature Range	-40~60C
Humidity	5~95%
Electrostatic Discharge (ESD)	+/- 15KV +/- 8KV
Shock Resistance	1.5g
EMI / RFI	FCC A CE
Regulatory	CDRH 2



OCBS-W011-B



www.ocominc.com

CE FC





OCBS-W011-B



www.ocominc.com

CE FC







OCBS-W011-B



www.ocominc.com

