

POS

OCBS-LA04

Table

Wavelength	650-670nm
Power	100mW
Beam Diameter	2.5mm @ 600mm, 100mm UPC / EAN
Beam Quality	M ²
Spot Size	0.10mm @ 4MIL, PCS 0.9
Modulation	20kHz @ 650nm
Compliance	UPC / EAN, UPC / EAN, UCC / EAN, 128, 39, 39, ASCII, 39, trioptic, 128, 128, ASCII, 2, 5, 2, 5, 93, 11, ATA, RSS, 2, 5 ...
Interface	PS2, RS232, USB
Voltage	DC + 5V ± 5%
Current	100mA
Power Consumption	< 40mW
Modulation Frequency	20kHz RS232
Beam Angle	45° - 60°
Dimensions	L165.42mm X W69.72mm X H89.67mm
Weight	140g
Material	Plastic
RoHS	Compliant
Operating Temperature	0°C - 50°C
Storage Temperature	-40°C - 70°C
Humidity	5% - 95% (non-condensing)
ESD Protection	±15kV (Human Body Model), ±8kV (Machine Model)
Shock Resistance	1.5ms
EMI / RFI	FCC A, CE
Regulatory	CDRH 2

Table

XXXXXXXXXX

Table

Information

Table