

OCBS-LA09

OCBS-LA09

OCBS-LA09	
OCBS-LA09	650nm
OCBS-LA09	200
CPU	32
OCBS-LA09	2.5 600 100 UPC / EAN
OCBS-LA09	50 @ 60mm 220 @ 200
OCBS-LA09	
OCBS-LA09	
OCBS-LA09	3mil / 5MIL
OCBS-LA09	30
OCBS-LA09	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)
OCBS-LA09	±65°; ±60°; ±42°
OCBS-LA09	
OCBS-LA09	PS2 RS232 USB
OCBS-LA09	5V DC ±5
OCBS-LA09	85; 100
OCBS-LA09	LED
OCBS-LA09	ABS + PC
OCBS-LA09	156 * 68 * 83 * * *
OCBS-LA09	235
OCBS-LA09	
OCBS-LA09	
OCBS-LA09	0°C 45°C
OCBS-LA09	-40°C 60°C
OCBS-LA09	5-90
OCBS-LA09	+/-15kV +/-8KV
OCBS-LA09	0 100,000 LUX
OCBS-LA09	1.5
OCBS-LA09	EN60825-1 1

OCBS-LA09

