

5.0rfid

M / NOCBs-D5000

Android 5.1.1
1GB RAM8GB ROM
5.0720 * 1280
IP65 / 1.5
3.7V8000mAh
8 MPLED
4G / Wifi / GPS /
HHW
1D / 2D
RFID LF / HF / UHF / NFC
TCS1SM

	170mmH×85mmW×23mmD±2mm
	380
	5.0TFT-LCD720x1280
	LED
	3 TP64
	2 PSAM1SIM1TF
	3.7V8000mAh
CHARACTERSTICS	
	A531.5GHz
	Android 5.1.1
	1GB RAM8GB ROMMicroSD32GB
	-20°C50°C
	-20°C70°C
	5RH 95RH
	5ft./1.5 m
	IP65 IEC
ESD	±15kv±8kv±8kv
SDK	HHW
	Java
	Android StudioEclipse
WWAN	TDD-LTE38,39,40FDD-LTE1,2,3 4,7; WCDMA850/1900 / 2100MHz; GSM / GPRS / Edge 850/900/1800 / 1900MHz;

WLAN		2.4G / 5GDual 天线IEEE 802.11 a / b / g / n / ac
WPAN		蓝牙 Class v2.1 + EDR蓝牙v3.0 + HS蓝牙v4.0
GPS		GPS蓝牙A-GPS蓝牙5
摄像头 CAPTUE		
摄像头 摄像头		
1D 识别	1D 识别 识别	识别 N431x
	识别	识别 识别
2D 识别	2DCMOSImager	识别 N6603
	识别	PDF417识别MicroPDF417识别RSS识别 TLC-39识别Datamatrix识别QR识别 Micro QR识别Aztec识别MaxiCode识别识别识别 PostNet识别识别识别识别 识别识别识别识别识别识别 识别
摄像头 摄像头		
摄像头	8 摄像头	
摄像头	摄像头 摄像头LED摄像头	
RFID 识别识别识别		
RFID 识别	识别	识别125KHz / 134.2KHz识别FDX-B / HDX识别
	识别	ISO 11784&识别; 11785
	R / W识别	2识别 识别10识别
RFID HF	识别	13.56MHz识别
	识别	ISO 14443A&识别; 15693
	R / W 识别	2识别 识别8识别
RFID 识别识别	识别	865识别868MHz识别 识别920识别925MHz
	识别	EPC C1 GEN2 / ISO 18000-6C
	识别 识别	识别 识别2DBI识别
	R / W 识别	1识别 识别1.5识别识别识别识别识别
识别 2.45GHz识别	识别 识别200识别识别识别	
433MHz识别	识别 识别200识别识别识别	
ZigBee识别 识别识别识别		
识别	IEEE 802.15.4识别识别	
识别 识别	100 识别200识别识别识别	
识别 识别识别识别		
识别	TCS15M	
识别 识别	识别 识别识别	
识别	508 DPI	
识别	FRR <0.008识别FAR <0.005识别	
识别	1000	
PSAM 识别识别识别		
识别	ISO 7816	
识别	9600识别 19200识别38400,43000,56000,57600,115200	
识别	2 识别识别	
识别		
识别	1xPower 识别	
	1x识别识别识别	
	1xDC 识别识别	
	1xUSB 识别识别	
识别	识别识别 UHF识别识别	