

□□□□□□□□□□□□□□□□□□

(OCBS-W230)

□□□□□, □□□□□□□□□□□□□□□□

□□:

□□□□□□□□300□, □□ 100m;

□□□□□□□□□□, □□□□□□□;

□□□□□□□□□□□□□□□□□□;

□□□□□□□□□□□;

□□□5□□□□□□;

□□□□□□□□□□□□□□□□

□□:

□□□□	617□□□		
□□□□	625□□□		
□□□□	39 (H) x ° (V)		
□□□□	0-360 °		
□□	±65		
□□□□	±60°		
□□□□□	□□25%		
1D	upc/supplementals, BooklandEAN, ISSN, UCC □□□□□□□□, Code128, GS1-128, ISBT 128, □□ 39, □□39□ ASCII, Trioptic □ □ 39, □□ 32, □□ 93, Code11, □□ 2 5, □□ 2 5, □□ 2of 5, Codabar, MSI, □□ 2 5, GS1 □□ Barvariants, □□ 3 5, ISBT Concat		
2D	PDF417, MicroPDF417, □□□, TLC-39,Data □□, □, QR □, MicroQR, □□□□		
□□	usb		
□□□□	□□: 100m; □□: 300m (□□)		
□□□□	-10 ° c-45 ° c		
□□□□	-20 ° c-65 ° c		
□□□□	5%-85%		
□□□□	5%-95%		
□□□	□□□□□1.8m □□□□□		
□□□□	DC 5V, 350mA		
Lumination	□□: 3.000 □□□□□; □□□□: 86000LUX □□		
emc	EN50081, par1 □□		
fcc	EN50082, par1 □□		
IP □□	IP42		
□□□□			
□□□□ *	□□□□□□		
	□□□□□□		
□□□□	□□□□	□□	□
□□39	5.0 □□	5mm	90mm
100% UPCA	13.0 □□	8mm	200mm
□□39	20.0 □□	8mm	250mm
PDF 417	6.8 □□	5mm	95mm
□□□□	10.0 □□	5mm	110mm
QR □	20.0 □□	10mm	150mm
□□□1D □□39	2.8 □□ (0.071mm)		
□□□2D □□□□	4.8 □□ (0.122mm)		
□□	ABS + PC		
□	95x65x155mm		
□□	160g		
□□□□□:	18.2X11.7X11.2cm		
□□□□□:	374g		



