

OCBS-2008 2d 0000000000000000

1111

LED	
CMOS	
640 * 480/256	
13mil UPC 40 /s	
50 °C; 20	
≥4mil	
1 D	UPC-A-EPC E1 EAN 13 EAN 8 (EAN) ISSN 39 ASCII 32 Trioptic 39 2 5 2 (5 2) 5 5 (NW7) 128 UCC/EAN 128 (GS1-128) ISBT 128 Code93 11 (8)/ 2
	PDF417 MicroPDF417 QR GS1
(5mil) 39:50 ~ 120 (10mil) 39:25 ~ 250 UPC/EAN (13mil): 20 ~ 320 Matrix(7.5mil):63 ~ 150 PDF417(6.6mil):62 ~ 145	
± 45 ° @0 ° 0 ° ±30 ° @0 ° 0 ° ± 45 ° @0 ° 0 °	
USB USB COM(virtual serial port)	
3.3 v ~ 5v	
2.0w (400mA)	
2.5 w (450mA)	
DC 5.5 v 1A	
I	
FCC 15 IEC60825-1 EN55022 B	
-20 °C ~ + 60 °C (-4 °C F 144 F)	
-30 °C ~ + 70 °C (-22 °C F 158)	
5%-95%()	
1.5 (5.0)	
IP54	
:	
156 * 68 * 83	
195 ()	
48 * 36 * 47 (20 13.5)	
48 * 39 * 52 (30pcs 15)	



