

□□□□□□□□□□□□□□

□□□□OCBS-

T007

□

□□□□

□□□□	
□□	650□□□□□□□□□□
□□□	□□□□□□
□	□□=□□□□□□□□□□□□=□□ □□
□□□□	□□KBW□RS232□USB
□□□□	
□□□□x□x□□	□□□□180 * 130 * 110 MM□□ □□□□□□230□□* 160□*120□□□
□□	□□□□460□□□□□□630 G□
□□□□	
□□□□	5VDC + / -10□
□□□□	1000MW□□200mAx5V□
□□□□	900mW□□180mAx5V□
□□□	□2:5 VDCx1A
□□□□□	□□1
□□	CE□RHOS□FCC□15□B□□□□EMC □□
□□□□	
□□□□	0degree C - 40□ç
□□□□	- 40□C-60□Ç
□□	5□□95□□□□□□□□□□
□□□□	□□□1.5□□□□□□□□□□
□□□□□	□□□□□□□□□□□□□□□□
□□□□	
□□□□	□□20□
□□□□	□□1120□
□□□□	□□30□□□□□□
□□□□□□□□□□□□□□□□	360°□60°□60°
□□□□	UPC/EAN/JAN, Code 39Full ASCII,Code128Full ASCII, Codebar, Code 2 of 5,Code93,Code11,MSI Plessey,Trioptic,GS1 Data Bar, Telepen.

□□□□□□



Omni-directional Laser Barcode Scanner OCBS-T007



Product Picture





Features

Small Size, BIG Performance

20 scanning lines and five directions;
1120 times per second reading speed;





Multiple/Single line scanning capability meet different requirements;
Multiple interfaces optional: KBW, RS232 or USB.



Blue LED lights, loud buzzer hints;
The base can rotate.





Appearance is concise and easy, stable performance.

All-round show





Parameter

Performance parameters	
Light source	650 nm visible laser diode laser
buzzer	Seven tones or silent
lamp	Blue = laser light, ready to scanner, Red = decoding success
System interface	PC kBW,RS232,USB
Physical parameters	
volume(Lx W x H)	Product size (180 * 130 * 110 mm), packing size:(230 mm * 160 mm * 120 mm)
Weight	Product size (460 g), packing (630 g)
Electrical parameters	
Input voltage	5VDC+/-10%
Work power	1000mW(200mAx5V)
standby power	900mW(180mAx5V)
direct-current source	Class 2:5VDCx1A
Laser level	Class1
identification	CE,RHOS,FCC Part 15 Class B, European Union EMC Directive
Environmental parameter	
operating temperature	0° C - 40° C
Storage Temperature	-40° C - 60° C

humidity	5% to 95% relative humidity (no condensation)
antiknock characteristic	To withstand from 1.5 meters high drop.
dust tightness	Seal to prevent air dust particle erosion.
Scanning parameters	
Scanning mode	Omni directional 20 line
Scanning speed	1120 times per second
printing contrast	Minimum 30% reflection difference
Roll(tilt),Pitch, Skew(yaw)	360°,60°,60°
Decoding ability	UPC/EAN/JAN, Code 39Full ASCII,Code128Full ASCII, Codebar, Code 2 of 5,Code93,Code11,MSI Plessey,Trioptic,GS1 Data Bar, Telepen.

Applications

OCBS-T007 is an aggressive, omnidirectional presentation laser bar code scanner. Designed for applications where counter space is at a premium, OCBS-T007 is the ideal presentation scanner for **retail, convenience, liquor and specialty stores**. In addition, OCBS-T007 unique, contoured shape allows it to be picked up and used as a hand-held when scanning large or bulky items. Lightweight and rugged, OCBS-T007 is small in size but BIG in performance.



Production Line



Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets

✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6

✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Certifications



Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protection film





Payment



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust



OCOM Technologies Limited, founded in 2007, is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation." We would like establish stable and reliable partnership with customers.

