

# USB QR OCBS-2103

## 功能

- /□□□□;
- ;
- LED / LCD□□□□□□□□

## 规格

□□□□		
□□□□		IOTC 0370 CHIP
□□□□		640×480□CMOS
□□		RS-232□9.6□115.2Kbps□□□USB 1.1□HID-KBW□HID-POS□
□□	2D	PDF417□Data Matrix□QR□
	1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128(Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14□Interleaved 2 of 5,Industrial 2 of 5□Standard 2 of 5, Matrix 2 of 5□GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14),Code 39(Include Code 39 FULL ASCII),Code 11,MSI-Plessey
□□□□		≥10□
□□		□□LED
□□□□		□□□□□□□□□□
□□□□		10□
□□□□□□		≥30□
□□□□		□□□68°□□□□42°□□□□54°
□□		0 - 100000 LUX
□□□□		1 W
□□		DC 5V□0.5A□AC 100□240V□50□60HZ
□□□□		□□□□□□□□
□□		127.3□□□□L□X111.5□□□□W□X94□□□□H□
□□		300□
□□		
□□□□		-10°C□+ 50°C
□□□□		-20°C□+ 60°C
□□		5□ - 95□□□□□□□□
□□□□		□□□□□□□□□□uTools□□□□
□□		FCC□15□□B□□CE EMC B□