

□□□□□□□□□□□□□□□□

□□

□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□;  
 □□□□□??□□□□□□□□□□;  
 □□□□□□□□;  
 KBW□RS232□USB□□□□;  
 □□□□;  
 □□□□□□□□□□□□□□□□;

□□□

□□ □□	
□□□□	□□□□□650-670nm□
□□□□□□	100 □□□□□
□□□□□	2.5 □600□□□100□UPC / EAN□
□□□□□□	□□
□□□□□	0.10□□□4MIL□□PCS 0.9
□□□□□□□□□	20%, □□□□□□@ 650nm□□
□□□□□□	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
□□□□□	
□□□□□□□□	PS2□RS232□USB
□□□□	DC + 5V +/- 5□
□□□□□□	100□□
□□□□□□	<40□□
□□□□	□□□□□□□□□□RS232□□□□
□□□□□	□□45°□□60°
□□□□□□□	L165.42mm □~xW69.72mm□~xH89.67mm
□□□□	140□ □□□□□□□□□□
□□□□	□□
□□□□	□□□□□□□□
□□□□□	
□□ □□□□	0 ~50 degre eC
□□ □□□□	-40~70degreeç
□□□□	5~95□□□□□□□□□□□□
□□ □□□□	□□ □±15kV□□□□□□+□□□□□8KV□
□□□□□□□□	□□□□ □1.5□ □□□□□□□□□□
□□□□□	
EMI / RFI□	FCC A□□CE
□□ □□□□□	CDRH 2□□□□□□□

□□□□□□□□

XXXXXXXX

XXXX

XXXXXXXXXXXXXXXXXXXXX

XX

XXX