

M / N OCBS -2012

Feautre

- ;
- ;
- 1D 2D
- ;
- 5mil
- ;
- ;

Table

Table	
Resolution	640 * 480,256
Light Source	LED 617 nm ± 10 nm
Intensity	0 ~ 100,000 LUX
Field of View	360° ± 60° ± 65°
Scanning Speed	300 scan /
Supported Codes	2D DataMatrix Matrix 2 of 5 MaxiCode MicroPDF417 MSI Code PDF417 QR Standard 2 of 5 Telepen TLC 39
	1D Pos Aztec BPO Pos Codabar Codablock Code 11 Code 39 Code 93 Code 128 / EAN128 Dutch Pos t EAN.UCC Com pos ite Interleaved 2 of 5 Japan Pos t Planet Plessey Code Pos tnet RSS UPC / EAN
Resolution	≥ 5mil
Field of View	360°
Field of View	65°
Field of View	75°
Interface	
Interface	RS232 / USB / USB COM
Power Supply	DC 5 V ± 5%
Current	190 mA
Wavelength	1.5
Wavelength	165
Dimensions	170 x 60 x 95
Operating Temperature	
Operating Temperature	-5°C ~ 65°C
Operating Temperature	-20°C ~ 70°C
Weight	5 - 95
Weight	150

Table



OCBS-2012





OCBS-2012





OCBS-2012





1. 目的

本製品の仕様、使用方法、注意事項、保証書、
お問い合わせ先、お問い合わせ先、お問い合わせ先

お問い合わせ先、お問い合わせ先、お問い合わせ先

2. 注意事項&保証

本製品の保証書、お問い合わせ先、お問い合わせ先

お問い合わせ先、お問い合わせ先、お問い合わせ先

お問い合わせ先 / t/western union / paypal / 中国の Aliexpress / 中国の Aliexpress / 中国の Aliexpress
http://www.aliexpress.com/store/403448?tracelog = minisite_CI

3. 価格

OCOM 中国の Aliexpress / 中国の Aliexpress / 中国の Aliexpress

中国の Aliexpress / 中国の Aliexpress / 中国の Aliexpress

12 + 1

30 DOA DOA

4.

T / T LC Western Union Escrow T / T Western Union Escrow Paypal .Escrow Alipay.com Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos tePay CartaSi 4B Euro6000

5.

6.

Eruopean

133 1300 02 500 50

OCOM

500 POS

O2 Star

1500 133

9 OEM / ODM

POS

FCC CE Soncap POA BIS

12 + 1

“”