

OCBP -004A / B

M / N OCBP -004A / B

OCBP

8 MB SDRAM 200 Mhz 32 RISC CPU 4 MB

OCBP

127 5

300 984' 25.4 1

Kiosk

TSPL-EZ TPLE TPLZ

| OCBP -004A | OCBP -004B |
|---|-------------------|
| 8 / mm 203 DPI | 12 / mm 300 DPI |
| | |
| 127 5 | 101.6 4 |
| 108 4.25 | 104 4.09 |
| 2794 110 | 1016 40 |
| | |
| 20-112mm 0.78"-4.4" | |
| 0.06~0.254 mm 2.36~10 mil | |
| 10~2,794 0.39"~110" | 10~1016 0.39"~40" |
| 127 5 | |
| 300 67 mm 1" 40 mm~110 mm 1.6"~4.3" | |
| | |
| 234 194.8 302.5 | |
| 3.1 6.83 | |
| 32 RISC CPU | |
| 4MB Flash Memory | |
| 8MB SDRAM | |
| SD 4 GB | |
| USB2.0 RS-232 Centronics 10/100 Mbps 802.11 b / g / n | |
| | |
| AC 100-240V 1A 50-60Hz | |
| DC 24V 2.5A 60W | |
| LED 1 1 1 LED 3 | |

