

15

TM-1502



5

LED

1024*768@60HZ

| | |
|--------|---|
| 型番 | TM-1502 |
| 重量 | 15.1kg |
| 幅 | 400mm |
| 高さ | 150mm |
| VESA | 75*75mm |
| 入力端子 | 8端子 |
| 消費電力 | 304.128(H)* 228.096(V) |
| ピッチ | 0.297*0.297 |
| 解像度 | 4:3 |
| 最大解像度 | 1024*768 |
| 輝度 | 250cd/m2 |
| コントラスト | 700:1 |
| 視野角 | 16.2M |
| 応答時間 | 135ms |
| 駆動時間 | 8ms |
| 駆動電圧 | 5V |
| 駆動電流 | ITO ITO FIT |
| 駆動電圧 | <8ms |
| 駆動電流 | 3H |
| 駆動電流 | 72% |
| 駆動電流 | >3500000 times |
| 駆動電流 | |
| I/O | 12V DC *1 USB *1 15PIN D-sub VGA *1 HDMI*1 *1 |
| 駆動電流 | |
| 駆動電流 | 0~40 |
| 駆動電流 | -10 ~ 60 |
| 駆動電流 | 10%~80% |
| 駆動電流 | 10%~90% |
| 駆動電流 | |
| 駆動電流 | 430*180*385mm/6.5kg |
| 4kg | 630*440*390mm/21kg |
| 駆動電流 | |
| 駆動電流 | 110-240V/50-60HZ DC12V/2.6A |
| 駆動電流 | USB VGA HDMI |
| 駆動電流 | |
| 駆動電流 | |
| 駆動電流 | CE ROHS CCC FCC |



TM1502





TM1502





TM1502







TM1502





□□□□

□□□□□□□□□□ □□ □ □□□□□

□□