

# TM-AA-5D

## Specifications

|          |                          |        |        |        |
|----------|--------------------------|--------|--------|--------|
| Capacity | 4000 PLU                 |        |        |        |
| PLU      | 3:3:3:4                  |        |        |        |
| PLU      | 71                       |        |        |        |
| PLU      | 22                       |        |        |        |
| PLU      | 32                       |        |        |        |
| PLU      | 3000                     |        |        |        |
| PLU      | -10°C + 55°C; 0°C + 40°C |        |        |        |
| PLU      | 85%RH                    |        |        |        |
| PLU      | AC 220V 50HZ             |        |        |        |
| PLU      | LED                      |        |        |        |
| PLU      | 5:5:7                    |        |        |        |
| PLU      | 30mm-60mm                |        |        |        |
| PLU      | 75mm / s                 |        |        |        |
| PLU      | RS232                    |        |        |        |
| PLU      | 381 * 428 * 500mm        |        |        |        |
| PLU      |                          |        |        |        |
| PLU      | 3kg                      | 6kg    | 15 kg  | 30kg   |
| PLU      | 1                        | 2g     | 5g     | 10g    |
| PLU      | 1/3000                   | 1/3000 | 1/3000 | 1/3000 |
| PLU      | 20g                      | 40g    | 100    | 200    |

## Barcode

