

□□□□□□□□□□

□CR7400□

□□□

□ISO 7811□AAMVA□CA DMV□□□□ ANS□□;  
 □ □□□□ USB□□□□□PS2□□□□□RS232□□□□□ ;  
 □□□□□□;  
 □□3□□□□□□□□□□75/210 BPI;  
 □□□50□□;

□□□□□

□□	170MMX44MMX42□□		
□□	0.2□□		
□□	+ 5V DV±5□		
□□□□	<10□□		
□□□	ISO7811□AAMVA□ CA DMV		
□□Pos ition	□□1	□□2	□□3
□□□□	210 BPI	75 BPI	210 BPI
□□□□	76□□□	37□□□	107□□□
□□	USB□□□□□PS2□□□□□RS232□□□□□		
□□□□	□□1.5□□		
□□□□	10~100cm / sec		
□□□□	500,000□ □□□□		
□□□	□□É□□0.5□□JSE□□□□		
□□	□□□ - 30°C□+70°C□□□ -20°C□+ 50°C		
□□	□□□0□□95□RH□□□20□□90□RH		



CR7400



[www.ocominc.com](http://www.ocominc.com)

CE FC





CR7400



[www.ocominc.com](http://www.ocominc.com)

CE FC





## 1. 產品介紹

1. 產品介紹  
 2. 產品特點  
 3. 產品應用

## 2. 產品特點

2. 產品特點  
 4. 產品規格  
 5. 產品包裝

6. 產品價格 / 7. 產品售後 / 8. 產品代理 / 9. 產品維修 / 10. 產品回收  
 11. 產品查詢 / 12. 產品訂購 / 13. 產品安裝 / 14. 產品培訓 / 15. 產品支持  
 16. 產品服務 / 17. 產品諮詢 / 18. 產品建議 / 19. 產品投訴 / 20. 產品評價

## 3. 產品規格

3. 產品規格  
 21. 產品規格 / 22. 產品參數 / 23. 產品性能 / 24. 產品兼容性

