

CR7400
CR7400

1

ISO 7811 AAMVA CA DMV ANS;
USB PS2 RS232;
3 75/210 BPI;
00,000

2

□□	170MMX44MMX42□□		
□□	0.2□□		
□□	+ 5V DV±5□		
□□□□	<10□□		
□□□	ISO7811□AAMVA□ CA DMV		
□□□□	Track 1	□2□	□3□
□□□□	210 BPI	75 BPI	210 BPI
□□□□	76□□□	37□□□	107□□□
□□	USB□□□□□PS2□□□□□RS232□□□□		
□□□□	□□1.5mm		
□□□□	10□100□□/□		
□□□□□	500,000□ □□□□		
□□□	□□Ë□□0.5□□SE□□□□		
□□	□□□ - 30°C□+70°C□□□ -20°C□+ 50°C		
□□	□□□0□□95□RH□□□20□□90□RH		

Harold Hu
OCOM
104 518054
www.ocominc.com www.possolution.com.cn;
sales14@ocominc.com;
Skype sales14@ocominc.com
MSN ocomsales14@hotmail.com;
Whatsapp 86.18948789890;
18948789890 ocomsales14;
86.18948789890;
QQ 1467261417;
0086.755.86053207-814;
0086.755.86053207-868