

# USB

## OCBS-2008

### Features

- 
- 
- 
- 4mil
- 
- SDK / API
- 
- 

### Specifications

Item		LED
Item		
Item		
Item		LED
Material		
Material		CMOS
Size		640 * 480 256
Pitch		13mil UPC40
Pitch		50; 20
Pitch		≥4mil
Code	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, Bookland EAN, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 2, 5, 2, 5, NW7, 128, UCC / EAN, 128, GS1-128, ISBT, 128, CODE93, 11, USD-8, MSI / Plessey
	2D	PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
Code		39, 5mil, 50, 120, 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145
Viewing Angle		±45° @ 0°, ±30° @ 0°, ±45° @ 0°
Interface		
Interface		USB, USB COM
Voltage		3.3V, 5V DC
Current		2.0, 400
Current		2.5, 450
DC		5.5V 1A
LED		
EMC		FCC, 15, IEC60825-1, EN55022 B
Temperature		
Temperature		-20 to +60, -4 to 144
Temperature		-30 to +70, -22 to 158
Humidity		5% - 95%
Shock		1.5 to 5.0
IP		IP54
Weight		
Weight		156 * 68 * 83
Weight		195
Weight		48 * 36 * 47CM, 20, 13.5
Weight		48 * 39 * 52CM, 30, 15KG

