USB | LAN | POS | OCPP-80E

||||||OCPP-80E

- 4. 100M
- 5. $\Box\Box 256$ kb NV Logo $\Box\Box\Box 2M\Box\Box\Box\Box$.

- 8.

	230mm/s[[[]260mm/s[[[]]
	79.5±0.5mm
	72mm
	Φ80mm
	0.06-0.08mm
	576/512/
	3.75mm[[[[[]]]]
0000	
	/36P/25P+USB /+USB+
	ANK□□:FontA:1.5*3.0mm/ FontB:1.1*2.1mm
	UPC-A/UPC-E/JA[]EAN13[]/JAN8[]EAN8/CODE39/ITF/CODABAR/CODE93/CODE128/QRcode
	$\label{lem:condition} $$ PC347 \ Standard Europe \ Canadian-PC850 \ Nultilingual \ PC860 \ Portuguese \ Canadian-PC863 \ Canadian-PC860 \ Portuguese \ Canadian-PC860 \ Portuguese \ Canadian-PC860 \ Portuguese \ PC863 \ Canadian-PC860 \ Portuguese \ PC863 \ PC8$
	French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866
	Cyrillic#2 PC852 Latin2
	PC858[]IranII[]Latvian[]Arabic[]PT151[]1251[]
	100□□
	256KB
Flash	
	AC110V/220V□50~60Hz
	DC 24V/2.5A
	DC 24V/2.5A
000/0	
	DO O ANTIA A
	DC 24V/1A
00/00	
	000-10~60°C000100-90°C
	001.25000000190×145×1430000×0×00

x x x

×

×

×

×

×

×

×

×