

24.GHz
OCBS -W600

OCBS

| | |
|------|--|
| OCBS | |
| OCBS | OCBS@ 650 nm-670nm |
| OCBS | 164* 67* 95* * * |
| OCBS | 130* 45* 129* * * |
| OCBS | ABS + TPR / |
| OCBS | 235 |
| OCBS | |
| OCBS | LED |
| OCBS | |
| OCBS | |
| OCBS | 60@ 30 98@ 100 |
| OCBS | 2.5-6000.90.25 |
| OCBS | 100/ |
| OCBS | 0.10400 PCS0.9 |
| OCBS | 1 /500 |
| OCBS | UPC / EAN ASCII Codabar Code 39 Code 128 Code 128 Full Code 93 MSI RSS of 5 |
| OCBS | 3.7V / 750mAh |
| OCBS | 3.0 |
| OCBS | 30 |
| OCBS | 100mA; 40mA |
| OCBS | 60°; 45° |
| OCBS | 30m |
| OCBS | 2.4G |
| OCBS | 16MB |
| OCBS | USB |
| OCBS | |
| OCBS | 0 50 -4070 |
| OCBS | 5-90 |
| OCBS | 1.5m |
| OCBS | 0100,000 |
| OCBS | ±12KV ±6KV |
| OCBS | CE FCC 2 RoHS |

OCBS



Wireless Barcode Scanner

OCBS-W600



Product Picture





Features

Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100scans/sec



Scan speed: 10000/second

Data transmission distance reaches 30m in open area;



Scan Time: 30hours



||| All-round show





Parameter

| PHYSICAL CHARACTERISTICS | |
|--------------------------------|---|
| Light Source | Visible Laser Diode (VLD) @ 650 nm-670nm |
| Scanner Dimensions(W * H * D) | 164mm * 67mm * 95mm |
| Receiver Dimensions(W * H * D) | 130mm*45mm*129mm |
| Material | ABS+TPR /Aluminium alloy |
| Weight | 235g |
| Scanning Mode | Hand-held; bidirectional Scanning Mode. |
| Indicator Light | LED Red and Blue |
| Buzzer | Buzzer Volume Adjustable |
| PERFORMANCE CHARACTERISTICS | |
| Width of Scan Field | 60mm@30mm (From engine face) 98mm@100mm (from engine face) |
| Depth of Scan Field | 2.5-600mm (Contrast 0.9 Density 0.25) |
| Scan Speed | 100 scans/sec |
| Scan Precision | 0.10mm (4mil) PCS0.9 |
| Bit Error Rate | 1/(5million) |
| Decode Capability | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5 |
| Battery | 3.7V/750mAh,Li-ion |
| Charge Time | 3.0 Hours |
| Scan Time | 30 Hours |
| Current | 100mA (working); 40mA(standby) |

| | |
|---|---|
| Angles | Pitch:60°; Tilt: 45° |
| Communication Distance | 30m |
| Memory | 2.4G |
| Communication Interface | USB ,RS232,PS2 |
| USER ENVIRONMENT CHARACTERISTICS | |
| Temperature | 0°C to 50°C (Operating), -40°C to 70°C (Storage) |
| Relative Humidity | 5%-90%(Non-Condensing) |
| Drop Specification | Withstands repeated 1.5m drops to concrete surface |
| Ambient Illumination | 0~100,000 LUX |
| Electrostatic Discharge | Conforms to ±12KV air discharge and ±6KV of contact discharge |
| Safety Certificate | CE, FCC, Class 2, RoHS |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



□□□□

□□□□□□□□□□□□□□□□

□□□