

USB2D

M / NOCBS-2009

- ñ
- ñ
- ñ
- ñ C
- ñ 4MIL
- ñ
- ñ
- ñ

	640 * 480 256gray
	2m
	630nm10nm+
	USBUSB COM
	TRIOPTICMSI / Plessey
	UPC-AUPC-EEAN-8EAN-13ISBNISSNTELEPENUCC / EAN-128
	5 128112525 INDUSTRIAL 2
	2of 55 NEC 23939ASCIICode 93/ NW7UK / PlesseyTLC39GS1
	DatabarRSS
2D	PDF417PDF417QRMAXICODEMartix

39	5MIL	50	120
UPC / EAN	13mil	20	320
	7.5mil	63	150
PDF417	6.6mil	62	145
45		30	
			LED

182 * 65 * 109	L * W * H
195	
	200
ABS + PC	
+ 5V + 5	
40	

-20°C	60°C
-30°C	70°C
0	95
IP54	
CE	FCC
	ROHS

[- 2009 1D / 2D](#)

[1D / 2D](#)



OCBS-2009



www.ocominc.com

CE FCC





OCBS-2009



www.ocominc.com









□□□□

ñ □□□□

ñ □□□□

ñ □□□□

ñ □□□

ñ POS□□

ñ □□□□

ñ □□termina

ñ □□

ñ □□□□

ñ POS□□□

ñ POS□□

ñ □□□

ñ □□□□

ñ □□□

□□□□

[OCOM](#) [POS](#) [Auto-ID](#) [TUV](#) OCOM 500 1

assurance guarantee

OCOM [POS](#) [Auto-ID](#) [TUV](#) OCOM 500 1

OCOM [POS](#) [Auto-ID](#) [TUV](#) OCOM 500 1

OCOM [POS](#) [Auto-ID](#) [TUV](#) OCOM 500 1