

15.6 15.1 Pos

(M/N:POS-G156W/A-G151W/A)

OCOM G156W/A/G151W/A POS 15.6/15.1 inch 13.3mm bezel IO.

Item

Processor Intel i3 i5

GPU RK3288

EMMC 8GB/16GB/32GB

Storage Msata SSD 64GB/128GB/256GB

Thickness 58mm/80mm

Display

MSR VFD220

Weight

Table

Item	POS-G156W/A	POS-G151W/A
Screen Size	15.6 inch POS	15.1 inch POS
Processor	Intel i3/i5	
GPU	RK3288	
EMMC	8GB/16GB/32GB	
Storage	Msata SSD 64GB/128GB/256GB	
Thickness	58mm/80mm	58mm/80mm
Display	MSR VFD220	
Weight	1.3kg/1.2kg	
Resolution	1366*768	1024*768
Brightness	250cd/m ²	
Refresh Rate	160Hz/150Hz	
Touch	5-point touch	
Camera	15.6 inch 13.3mm bezel 1366*768	15.1 inch 1024*768
MSR	2*20 VFD	

Windows J1900	□□	Intel Celeron Bay Trail J1900 2.0GHz □ Intel core I3 / I5 4 th □ □□□□ CPU
	□□□□	1*SO-DIMM DDRIII□□□□□1333*/1600 4GB□□□□2GB/8GB□□
	□□□□	Msata SSD 64GB □□□□□□ 256GB
	□□	□□Real Tek ALC662□□□□
	□□□	10/100Mbps,Realtek RTL8111F □□□□□ □□Mini PCI-E□□□□□□□□WIFI□□
	□□□□	Windows7/8/10□□□□□WEPOS, Linux
□□RK3288	□□	□□□RK3288□□□□□1.8G□RK3399□□
	□□□□	□□ DDRIII 2GB□4GB □□
	□□□□	□□ 16GB EMMC□32GB □□
	□□	□□Real Tek ALC5640□□□□
	□□□	10/100Mbps,Realtek RTL8111F □□□□□
	WIFI&BT□□	□□Wi-Fi 802.11b/g/n□□□BT3.0/BT4.0
	□□□□	□□7.1□□□□□8.1
□□□		
Windows □ Android(J1900&RK3288)		□□□*1 12V DC □□□□*1 □□□RS232□* 1 □□□□RJ-45*1 USB *5 □□□ □*1 , □□□□*1
Windows□J1900□		LPT *1 VGA(15Pin D-sub)*1 □□□RJ11 *1 □□□□ PS/2 *1 □□□□□□□
□□ (RK3288)		□□ RJ11 □□□□ *1 ,RJ11 □□□□□ □□□□□□□ *1□□□□□ TF□□*1
□□		
80mm□□□□□		□□□□□□□ 150mm/s □□□□ 79.5- / 0.5mm □□□□□□□□□□ 72mm □□□□□□□□□□100km USB□□
58mm□□□□□		□□□□□□□ 80mm/s □□□□ 57.5- / 0.5mm □□□□□□□□□□ 48mm □□□□□□ 50km LPT □□
MSR		□□□□ MSR □□□□ 15.6 □□
□□□□□□		□□□□□□□□□□□□□□□□
□□□		□□ 80hm/5W □□□□□□□□
□□		
□□		15.6□□□□6.5Kg□□□□8.5Kg
□□□□□□□□		300*465*500mm

□□	
□□□□	0□40□□□
□□□□	-10□60□□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□	110-240V/50-60HZ □□□□ □ □□DC12/5A □□□□□□□□ W/o □□ □□ W/ 58mm □□□ DC12V/7A □□□□ W/80mm □□□□□□□□
□□□	□□□□□□□□□/□□/□□□□□□□□
□□	□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/□□□□/CCC

All In One Touch Screen POS System



SUPPORT SYSTEMS



WINDOWS



ANDROID



LINUX

Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



15.6 or 15.1 inch zero-bezel touch screen for optional

Multi-point projected capacitive touch panel

Built-in 58mm or 80mm thermal printer for optional

Ture flat and water-proof scratch-resistant surface display

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch


2*20 VFD

Product Interface


Windows interfaces J1900




DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0*1



USB 2.0*4



PS/2



MIC-IN



LIN-OUT


Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0*4



USB 3.0*1



MIC-IN



LIN-OUT


Android interfaces RK3288




DC



COM



LAN



RJ11(optional)*2



USB 3.0*1



USB 2.0*4



TF Card



MIC-IN



LIN-OUT

Product Color



Product Details





OCOM

OCOM 500 Auto-ID

OCOM POS POS ISO CE FCC BIS

2007 OCOM ISO9001 2008 159

Certifications



□□□□□□□□

- □□□□□□□□ POS □□□□□□□□□□□□
- □□□□500□□□□□□□□
- □□□□□□□□□□□□O2□□□□□□
- 2600□□□□□□□□163□□□□□□
- □□□□□□□□□□□□24□□□□□□□□□□
- □□□□□□□□□□□□15□OEM/ODM□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□□
- 121□□□□□□□□□□□□□□□□□□□□□□
- □□“□□□□□□□□”
- □□□□“□□□□□□□□□□□□□□□□□□□□□□□□”□□□□□□□□

□□□□□□□□

5. □□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□