

# Windows 10 3QRpos80

OCPP -80V

1DQRPDF417

200mm / s

100

256KB NV128KB

IAP

OPOS / J POS

100

ESC / POS	ESC / POS
576dots / line512dots / line	576dots / line512dots / line
max = 72mm.	max = 72mm.
USBUSB + LANURLBT WiFi	USBUSB + LANURLBT WiFi
200mm / s.	200mm / s.
80	80
0.060.08mm.	0.060.08mm.
DIA Ø83	DIA Ø83
256kbytes.	256kbytes.
NV Flash. 128kbytesUSB 64KB	NV Flash. 128kbytesUSB 64KB
12 * 24B9 * 17	12 * 24B9 * 17
GB18030Big5 24x24dots	GB18030Big5 24x24dots
PC347PC850PC860PC863PC865WPC1252PC866pc8522PC858PT1511251	PC347PC850PC860PC863PC865WPC1252PC866pc8522PC858PT1511251
1D. UPC-A / UPC-E / JAN13EAN13/ JAN8EAN8/ CODE39 / ITF / CODABAR / CODE93 / CODE128	1D. UPC-A / UPC-E / JAN13EAN13/ JAN8EAN8/ CODE39 / ITF / CODABAR / CODE93 / CODE128
2D. QRPDF417USB	2D. QRPDF417USB
100.	100.
AC 100V-240V 50 / 60Hz	AC 100V-240V 50 / 60Hz
DC 24V / 2.5A	DC 24V / 2.5A
0°C45°C1080RH	0°C45°C1080RH
-10°C-60°C1090RH	-10°C-60°C1090RH

CD	CD
190.16d x 140w x 134.64h mm	
1	
Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS	
SDK.	Android/iOS.







