Windows 10 3 | QR | DOS80 | DO

||||||OCPP -80V||

0001D000QR0PDF4170000

200mm / s

100

256KB NV[][][128KB[][]

___IAP____

 $\ \ \, \square\square\mathsf{OPOS} \ / \mathsf{J} \ \mathsf{POS}\square\square\square\square\square$

ESC / POS		
S76dots / line[512dots / line		
Max = 72mm.		
DOD		
USB_USB + LAN_URL_BT WiFi		
200mm / s. 200mm / s. 80		USB_USB + LAN_URL_BT WiFi
		200mm / s.
		80[
		0.06∏0.08mm.
DOC DOC	□□DIA	0000 Ø8300
NV Flash. 128kbytes[]][]USB 64KB[] [][][][][][][][][][][][][][][][][][][]		
Color		256kbytes.
GB18030 Big5 24x24dots	NV Flash.	128kbytes[][]USB 64KB[]
GB18030 Big5 24x24dots		\[\] \[\]
PC347[]]]]]]]]]]]]]]]]]]]]]PC850[]]]]]]]]]PC860[]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]		GB18030 Big5 24x24dots
pc852[]][]2[] PC858[]][][][][][][][][][][][][][][][][][]	00/00	
PC858PT1511251		PC347@annaannaanPC850mnaanPC860mnaannPC863maannaanPC865mnaannaannaannaannaaWPC1252mPC866mnaannaannaannaannaannaannaannaannaann
1D. UPC-A / UPC-E / JAN13 EAN13 / JAN8 EAN8 / CODE39 / ITF / CODABAR / CODE93 / CODE128		
2D. QR00PDF417000USB00000	1D.	UPC-A / UPC-E / JAN13[]EAN13[]/ JAN8[]EAN8[]/ CODE39 / ITF / CODABAR / CODE93 / CODE128
	2D.	QRNNPDF417NNUSBNNNNN
		000000000000000000000000000000000000000
□□ AC 100V-240V 50 / 60Hz		AC 100V-240V 50 / 60Hz
□□ DC 24V / 2.5A		DC 24V / 2.5A
0°C[45°C]10[]80[]RH	0000	0°C[]45°C[]10[]80[]RH
		-10°C-60°C[]10[][90[]RH

	190.16[]d[]x140[]w[]x134.64[]h[]mm
	100
	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS
SDK.	Android∏iOS.









