

**Windows 15/12 POS**

**M / N POS -C15**

**Spec**

- Windows Intel Celeron J1900 2.0GHz CPU
- Android 2.0GHz A83T ARM 8 Cortex-A7
- 2GB RAM + 8GB ROM Android
- 2GB RAM + 32GB SSD Windows
- 5
- 58 / 80mm
- 
- VFD

**Spec**

- 
- 
- 
- 

**Spec**



**Table**

|             |                                  |                    |
|-------------|----------------------------------|--------------------|
| Model       | POS -C15                         |                    |
| Series      | POS                              |                    |
| Processor ① | Intel Celeron J1900 2.0 GHZ      |                    |
| Processor ② | 2.0GHz A83T ARM 8 Cortex-A7      |                    |
| RAM ①       | DDRIII 1066/1333 * 1 2GB Windows |                    |
| RAM ②       | 2GB RAM 8GB ROM Android          |                    |
| OS ①        | Windows 7                        |                    |
| OS ②        | Android 5.1                      |                    |
| Storage     | SSD 32GB Windows                 |                    |
| Display     | 15" TFT LCD                      |                    |
| Brightness  | 350cd / m <sup>2</sup>           |                    |
| Resolution  | 1024 * 768                       |                    |
| Thickness   | 5mm                              |                    |
| Dimensions  | Depth                            | 203DPI             |
|             | Width                            | ESC / POS          |
|             | Height                           | 60mm               |
|             | Weight                           | 580g / 800g        |
|             | Mounting                         | 60mm / s 150mm / s |
|             | Material                         | MCBF               |
| Barcode     | MSR / VFD 220mm / 100mm          |                    |
| Power       | 15W; 14W                         |                    |

|            |                                  |
|------------|----------------------------------|
| I / O      | 1 * 12V DC * 1                   |
|            | HDMI * 1                         |
|            | VGA 15Pin D-sub * 1              |
|            | LAN RJ-45 * 1                    |
|            | USB 2.0 * 4                      |
|            | RS232 * 2                        |
|            | MIC IN * 1 * 1                   |
| I / O A83T | RJ11 * 1                         |
|            | TF * 1                           |
|            | RJ45 * 1                         |
|            | HDMI                             |
|            | DB9 RS232 * 1 USB * 2            |
|            | * 1                              |
|            | 0°C ~ 40°C                       |
|            | -20°C ~ 60°C                     |
|            | Windows XP Embedded WE POS Linux |
|            | 110-240V / 50-60HZ DC12 / 5A     |