

□□	POS-G156 □/□
□□	15.6□□□□□□□□pOs□□
□□	□□□□□□□
□□	□□□□□□□□□□□□□□
□□□	15.6□□□□□□□□
□□	1366*768
□□	25 0cd/□ ²
□□ A □□□	□□□□1 60 ;□□□1 50
□□ s □□	□□ □□GG □□□□□
□□□□	15.6□□□□□□□13.3□□□□□□W / □□□□□□□□□□1366*768□□
□□□□	2*20 VFD□□□□□□□□□□
□□	□□□ □□ Bay Tra□□l J1900 2.0GHz □ □tel core I3 / I5 4 th □□CPU □□□□
□□ □□	1*SO-DI□□□M DDRIII □□□□□1333*/1600 4GB□□□□□2GB/8GB□□
□□□□	Msata SSD 64GB □□□□□□ 256GB
□□□□	□□Real Tek ALC662□□□□□
□□□□	10/100Mbs,Realtek RTL8111F □□□□□ □□Mini PCI-E□□□□□□□□□□WIFI□□
□□□□	□□ 2010 □ 7 □ 8 □□ □□□□WEPOS, Linux
□□	□□□□□ □□□□RK3568 , RK3 288□RK3399 □□□□
□□ □□	□□DDRIV 2GB□4GB□□□□□
□□□□	□□16GB EMMC□32GB□□
□□□□	RJ45□□□□ 10/100Mbs □□□□
WIFI&□□□□	□□ □□□□ 802.11b/g/n ,BT3.0/BT4.0□□
□□□□	Android 7.1□□□□Android 8.1 Android 11
□□ □□ Android(J1900&RK3568) □	p □□ □□*1
	12V DC □□□□*1
	□□(RS232) * 1
	□□□□RJ-45*1
	USB * 5
	M □□□□ in *1 , □□□□*1
□□□□J1900□	□□□□*1
	VGA(15□□D-sub)*1
	RJ11 □□*1 □□□□□
	PS/2 *1 □□□□□□□
□□□□RK3568□	□□□□ RJ11 □□*1 ,RJ11□□□□□□□□□□*1□□□□
	TF□□*1□SIM□□*1
80□□□□□□□□	□□□□□□□
	150mm/s □□□□□
	79.5- / 0.5mm□□□□□□□□□□72mm
	□□□□□□□□□□□□□□□□100km
	USB□□
58□□□□□□□□	□□□□□□□
	80mm/s □□□□□
	57.5- / 0.5mm□□□□□□□□□□48mm
	□□□□□□□50km
	LPT□□
MSR	□□□□ MSR □□□□15.6□□

□□□□	□□□□□□□□□□□□□□□□
□□□	□□80hm/5W□□□□□□□□
□□	
□□	□□6.5□□, 15.6□□□□8.5Kg
□□□□□□□□	300*465*500□□
□□	
□□□□	0 □ 40 □□□
□□□□	- 10 □ 60 □□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12/5A □□□□□□□□□□□□□□ □58mm□□□□DC12V/7A □□ □□□□□□□□ W/80mm □□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	□□□□□□□□□□□□□□ □□□
□□	
□□	FCC A □□/CE □□/ LVD/CCC

Product Color



Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2*20 VFD

SUPPORT SYSTEMS



WINDOWS



ANDROID




LINUX

Product Interface


Windows interfaces J1900




DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0*1



USB 2.0*4



PS/2



MIC-IN



LIN-OUT


Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0*4



USB 3.0*1



MIC-IN




LIN-OUT


Android interfaces RK3288




DC



COM




LAN



RJ11(optional)*2



USB 3.0*1



USB 2.0*4



TF Card



MIC-IN



LIN-OUT



All In One Touch Screen POS System



Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



Product Details

