

OCPP - M05



Features

Windows, Android, iOS, Android + iOS

USB, RS232

90mm/h

TPH 100mm

OCPP - M05

规格书

规格书××××	105×75×45mm
重量	134g
厚度	4mm
分辨率	480p
接口	USB
接口	支持ESC / POS
接口	支持90°/0°
接口	8mm / mm203 dpi
接口	12x24 / 24x24
接口	32mm / 16mm
接口	1.5 x 3.0 mm2x2mm/3.0 x 3.0 mm2x2mm
接口	58.0±0.1mm x40.0mm
接口	0.06mm/0.08mm
接口	支持/不支持
接口	USB/RS-232/红外线
接口	256KB
接口	9 V CC / 2 A.
接口	7.4 V DC / 1500 mA;支持4-5mm红外线120-150mm
接口	支持红外线
接口	支持-10°C~50°C支持10°~90°
接口	支持-20°C~70°C支持5°~95°
接口pos支持dis	支持30°ASCII/支持
接口	支持“1234”支持6mm
接口	3.5 * 1.1mm







[illegible]

► Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant



□□□□□□□□



□□

1. □□□□□□□□ DHL □□□□□□ UPS □ EMS □ TNT □□
2. □□□□□ 3-7 □□□□□□□
3. POS TA INTERNATIONAL AIR □□□□□ 2-4 □□□□□□□□□□
4. □□□□□□□□□

□□

1. □□ T / T.
2. □□□□
3. PayPal

□□
□□□

12pos24

MOQpos

2.&

pos

t / twestern uionpaypalaliexpress
http://www.aliexpress.com/store/403448 Tracelog = minisite_CI

3.

Global Fortune 5001100

12 + 1pos24;

30DOA DOA

4.

5.

6.

Eruopean.....

1331300500O250

OCOM

1. 02 Star

1500 133;

9 OEM / ODM

POS

pos

FCC CE Soncap POA BIS

12 + 1

“ ”