

12v POS

OCPP-58E



OCPP-58E OCPP-58E

12v pos POS

-
-
- ◆
- ◆
- ◆ GB18030
- ◆
- ◆ LOGO
- LOGO
- ◆ Windows Linux Android IOS

--	--

□□□□	□□□□	□□
	□□□□	48MM
	□□□	384dots / □□8dots / □□□203DPI□
	□□□□	90□□/□
	□□□□	USB□USB +□□
	□□□	3.75□□□□□□□□□□□□□□
	□□	□□A□32□□□□/□ □□B□42□□□□/□ □□□□□□□□16□
	□□	□□GB18030□□/□□□□□□□
	□□□□	ANKcharacter□□□A□1.5×3.0mm□12×24□□ □□B□1.1×2.1mm□9×17□□□□/□□□□□□3.0×3.0mm□24×24□□
	□□□□	□□□□□□□
□□		UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□CODE39 / ITF / CODABAR / CODE93 / CODE128
□□□□	□□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60mm
	Feed□□	□□□□□Clameshell□□□□
□□□□	□□	ESC / POS
□□	□□□□□□	□□□AC 100V-240V□50-60Hz □□□DC 12V / 2A
	Casher□□□□	DC 12V / 1A
□□	□□□□□□	4K
	NV Flash	40K
□□□□	□□	590□
	□□	185 * 130 * 112□MM□
□□	□□	□□□5□45°C□□□□10□80□
	□□	□□□-10□50°C□□□□10□90□□□□□□
□□□□□□	□□□□□□	50KM□□□□□□≤12.5□