

# 12v

## (OCPP-58E)



OCPP-58E

OCPP-58E , , , , OCPP-58E , , .

printer, 12v

, , .

,

, ;

, ;

GB18030 ,

, ;

& ;

windows Linux Android IOS

, , , , , , , ,

			48MM
			384/ (8 /, 203 dpi)
			90/
			usb, usb +
			3.75 mm ( )
			A:32 / B:42 / Chinese-16
			GB18030 /
			ANKcharacter, : 1.5×3.0mm (12×24dots) B: 1.1×2.1mm (9×17dots) /: 3.0×3.0mm (24×24)

□ □□□□	□□ □□□	PC437/□□□/PC850/PC860/PC863/PC865/WestEurope/□□/□□□ □/EastEurope/□□/ WPC1252/PC866/PC852/PC858/IranII/□□□□/ □□□□/PT151,1251/PC737/□ □/1257/ThaiVietnam/PC864/PC1001/(□□□ □)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(□□□)/(□□□)
	□ □□	upc-JAN13 (EAN13)/JAN8 (EAN8) CODE39/□□/ CODABAR/CODE93/CODE128
□□ □□	□□ □□	□□ □□□□□□
□□	□□	□ □
	□□	57.5±0.5mm
	□□	≤60mm
	□□ □□	□□ □□ (Clameshell □□)
□□ □□	□□	ESC/POS
□□	□□ □□□	□□: AC 100 v-240 v, 50-60Hz □□: DC 12□/2 a
	□□ □□□□	□□ 12□/1 a
□□□	□□ □□□	4K
	□□□□ □□	40K
□□ □□	□□	590g
	□	185 * 130 * 112 (MM)
□□	□□	temp:5 ~ 45°C, humidity:10 ~ 80%
	□□	temp:-10 ~ 50°C, humidity:10 □ 90% (□□□□)
□□□ □□	□□ □□□□	50□□ (□□ density≤12.5)



OCPP-58E



[www.ocominc.com](http://www.ocominc.com)





OCPP-58E



[www.ocominc.com](http://www.ocominc.com)

