

58mm POS58 pos

(OCPP-58E)



OCPP-58E

OCPP-58E status,OCPP-58E

pos 58mm pos

OCPP-58E

OCPP-58E

OCPP-58E

OCPP-58E

OCPP-58E

OCPP-58E GB18030

OCPP-58E

OCPP-58E &

OCPP-58E Linux Android IOS

OCPP-58E

OCPP-58E

OCPP-58E

OCPP-58E	OCPP-58E
OCPP-58E	OCPP-58E
OCPP-58E	48MM
OCPP-58E	384 (8, 203 dpi)
OCPP-58E	90
OCPP-58E	usb, usb +
OCPP-58E	3.75 mm
OCPP-58E	A:32 B:42 Chinese-16
OCPP-58E	GB18030
OCPP-58E	ANKcharacter, 1.5x3.0mm (12x24dots) B: 1.1x2.1mm (9x17dots) 3.0x3.0mm (24x24)

□ □□□□	□□ □□□	PC437/□□□/PC850/PC860/PC863/PC865/WestEurope/□□/□□□ □/EastEurope/□□/ WPC1252/PC866/PC852/PC858/IranII/□□□□/ □□□□/PT151,1251/PC737/□ □/1257/ThaiVietnam/PC864/PC1001/(□□□ □)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(□□□)/(□□□)
	□ □□	upc-JAN13 (EAN13)/JAN8 (EAN8) CODE39/□□/ CODABAR/CODE93/CODE128
□□ □□	□□ □□	□□ □□□□□□
□□	□□	□ □
	□□	57.5±0.5mm
	□□	≤60mm
	□□ □□	□□ □□ (Clameshell □□)
□□ □□	□□	ESC/POS
□□	□□ □□□	□□: AC 100 v-240 v, 50-60Hz □□: DC 12□/2 a
	□□ □□□□	□□ 12□/1 a
□□□	□□ □□□	4K
	□□□□ □□	40K
□□ □□	□□	590g
	□	185 * 130 * 112 (MM)
□□	□□	temp:5 ~ 45°C, humidity:10 ~ 80%
	□□	temp:-10 ~ 50°C, humidity:10 □ 90% (□□□□)
□□□ □□	□□ □□□□	50□□ (□□ density≤12.5)



OCPP-58E



www.ocominc.com





OCPP-58E



www.ocominc.com

