□□□ 58mm POS58 □□ pos □□□

(OCPP-58E)



pos [][], 58mm [][][], pos [][][]

000000, 00000000;

00 00	
	48MM
	384□/□ (8 □/□□, 203 dpi)
	9000/0
	usb, usb + □□
	3.75 mm ()
	□□ A:32 □□/□
	□□ B:42 □□/□
	Chinese-16
	□□ GB18030 □□/□□□□□□
	ANKcharacter, □□ □: 1.5×3.0mm (12×24dots)
	\square B: 1.1×2.1mm (9×17dots) \square / \square \square : 3.0×3.0mm (24×24 \square)

	00 000	PC437/\ \ \ \PC850/PC860/PC863/PC865/WestEurope/\ \ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
		1
		□/EastEurope/□□/WPC1252/PC866/PC852/PC858/IranII/□□□□/
		□/1257/ThaiVietnam/PC864/PC1001/(□□□
		□)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(□□)/(□□)
		upc-JAN13 (EAN13)/JAN8 (EAN8) CODE39/□□/
		CODABAR/CODE93/CODE128
	00 00	
		57.5±0.5mm
		≤60mm
		□□ □□ (Clameshell □□)
		ESC/POS
		□□: AC 100 v-240 v, 50-60Hz
		□□: DC 12□/2 a
	00 0000	□□ 12□/1 a
	00 000	4K
	0000 00	40K
		590g
		185 * 130 * 112 (MM)
		temp:5 \sim 45°C, humidity:10 \sim 80%
		temp:-10 ~ 50°C, humidity:10 ☐ 90% (☐☐☐)
	00 0000	50□ (□ density≤12.5)



