

USB QR

OCBS-2009

;
 ;
 ;
 ;
4mil;
 ;
 ;
 ;

;

Parameters	
尺寸	640 * 480 256gray
分辨率	200 * 150
厚度	2.0mm
波长	630nm ± 10nm+
接口	USB COM
1D	TRIOPTIC / Plessey UPC-A / UPC-E / EAN-8 / EAN-13 / ISBN / ISSN / ISBT / TELEPEN UCC / EAN-128 / 128 / 11 / 5 2 / 5 2 INDUSTRIAL 2 / 2 of 5 / NEC 5 2 39 / 39 / ASCII / 93 / NW7 / UK / Plessey TLC39 / GS1 Databar / RSS
2D	PDF417 / QR / MAXICODE Martix / F
分辨率	5MIL / 50 / 120 UPC / EAN / 13mil / 20 / 320 7.5mil / 63 / 150 PDF417 / 6.6mil / 62 / 145
厚度	45 / 30
光源	LED
尺寸	
尺寸	182 * 65 * 109mm L * W * H
重量	195g
厚度	2.0mm
材料	ABS + PC
DC	+ 5V + 5
厚度	40mm
温度	
工作温度	-20 C ~ 60 C
存储温度	-30 C ~ 70 C
湿度	0% ~ 95%
防护等级	IP54
认证	CE / FCC / ROHS



OCBS-2009



www.ocominc.com





OCBS-2009



www.ocominc.com







Tag: 2D barcode reader,high speed scanner