

000000;

00000000;

4mil____;

Parameters	
	640 * 480 256gray [
	20 00 0
	[][] 630nm[10nm[+
00 00	
0001D	[] [] [] TRIOPTIC[MSI / Plessey]
	UPC-A[] UPC-E[] EAN-8[] EAN-13[] ISBN[] ISSN[] ISBT[] TELEPEN[]
	UCC / EAN-128 128 0 0 11 0 5 2 0 5 2
	INDUSTRICAL 2 [] [] 2of 5[NEC 5 2]
	390 390 0 ASCII093000 / NW70UK / Plessey0
	TLC39[] GS1 Databar[] []RSS[]
2D	PDF417[] PDF417[] QR [] MAXICODE[] [] [] [] [] [] [] [] [] [] [] [] [] [
	Martix 00 00 000 F0 000 00
	39D D5MILDD50DDD120DD
	UPC / EAN []13mil[][20][][320][]
	00 00 07.5mil00630015000
	PDF417 [6.6mil][62][145][
	450 0000 300 000
0000	102 * CF *100FF FI * W * HF
	182 * 65 *109[] []L * W * H[]
	1950 00 000
00 0 00	
00 000	ABS + PC[] []
DC [[[[]]	+ 5V + 5[]
	40
0000	20 CEGO C
	-20 C[60 C
	-30 C[]70 C
	00 0 950 0000
0000	



OCBS-2009



www.ocominc.com











OCBS-2009



www.ocominc.com











Tag: 2D barcode reader, high speed scanner