

usb2d

OCBS -LA09

	650nm
	200
	32
	2.5~600mm100UPC / EAN
	50mm @ 60mm220mm @ 200mm
	3mil/ 5mil
	30
	UPC / EANUPC / EANUCC / EAN 128Code 39Code 39ASCIITrioptic Code 39Code 128Code 128 Full ASCIICodabarInterleaved 2 of 5Discrete 2 of 5Code 93MSICode 11RSS2 of 5MSI / PlesseyUK / PlesseyUCC / EAN 128GS1 DataBarRSS
	±65°; ±60°; ±42°
	PS2RS232USB
	5V DC±5
	85 mA; 100
	LED
	ABS + PC
	156 * 68 * 83 mm* * *
	235
	0°C45°C
	-40°C60°C
	5-90
	+/- 15KV+/- 8KV
	0~100,000 LUX
	1.5
	EN60825-1Class 1





Features

Simple but not easy

200scan/sec high scan rate and
long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined
with future-proofing





Competitive price for 32bit model



||| All-round show





Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
User Environment	
Operating Temperature:	0℃~45℃
Storage Temperature:	-40℃~60℃
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

4. 注册账号&密码

注册账号和密码的步骤如下：
1. 访问 [t / t.western union paypal](http://t.westernunion.com/paypal) 页面。
2. 点击 **aliexpress** 按钮。
3. 输入 <http://www.aliexpress.com/store/403448> 并点击 **tracelog**。
4. 输入 **= minisite_Cl** 并点击 **factorie**。

5. 注册账号

* 注册账号的步骤如下：
1. 输入 **12000** 并点击 **1**。
2. 输入 **2** 并点击 **3**。
3. 输入 **4** 并点击 **CRM**。
4. 输入 **5** 并点击 **6**。
5. 输入 **7 * 24** 并点击 **4**。
6. 输入 **12** 并点击 **12**。

6. 下载

下载 SDK 的步骤如下：
1. 访问 [http:// www pos solution.com.cn/cn/download.html](http://www.pos-solution.com.cn/cn/download.html)。
2. 点击 **SDK** 按钮。

7. 安装

安装 SDK 的步骤如下：
1. 访问 [http:// www pos solution.com.cn/video.html](http://www.pos-solution.com.cn/video.html)。

8. 测试

测试 SDK 的步骤如下：