

□□□□□□□□□□□□□□
(OCBS-W230)

11

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □

0000	61700000		
0000	62500000		
0000	39 (H) x ° (V)		
0000	0-360 °		
00	±65		
0000	±60°		
00000	0025%		
1D	upc/supplementals, BooklandEAN, ISSN, UCC 0000000, Code128, GS1-128, ISBT 128, 00 39, 0039 ASCII, Trioptic 0 39, 00 32, 00 93, Code11, 00 2 5, 00 2 5, 00 2of 5, Codabar, MSI, 00 2 5, GS1 00 Barvariants, 00 3 5, ISBT Concat		
2D	PDF417, MicroPDF417, 000, TLC-39,Data 00, 0, QR 0, MicroQR, 0000		
00	usb		
0000	00: 100m; 00: 300m (00)		
0000	-10 ° c-45 ° c		
0000	-20 ° c-65 ° c		
0000	5%-85%		
0000	5%-95%		
000	000001.8m 00000		
0000	DC 5V, 350mA		
Lumination	00: 3.000 00000; 0000: 86000LUX 00		
emc	EN50081, par1 00		
fcc	EN50082, par1 00		
IP 00	IP42		
0000			
0000 *			
000000			
000000			
0000	0000	00	0
0039	5.0 00	5mm	90mm
100% UPCA	13.0 00	8mm	200mm
0039	20.0 00	8mm	250mm
PDF 417	6.8 00	5mm	95mm
0000	10.0 00	5mm	110mm
QR 0	20.0 00	10mm	150mm
0001D 0039	2.8 00 (0.071mm)		
0002D 0000	4.8 00 (0.122mm)		
00	ABS + PC		
0	95x65x155mm		
00	160g		
0000:	18.2X11.7X11.2cm		
0000:	374g		



