

□□□□□□□□□□□□

□□□□□□-W230□

□□□

□□□□	617□□LED
□□□□	625□□LED
□□□□	39°□H□×25°□V□
□□□□	0 - 360°
□□	±65°
□□	±60°
□□□□□□	□□25□
1D	UPC / EAN□□UPC / EAN□□□□BooklandEAN□□ISSN□□UCC□□□□□□□□□□Code128□□GS1-128□□ISBT 128 □□39□□39□□ASCII□□Trioptic 39□□32□□93□□Code11□□□□□□2 5□□□□2 5□□□□2of 5□□□□□□□□□□5□□□2□□GS1 □□Barvariants□□□□3 5□□□□□□□□Concat□
2D	PDF417□□MicroPDF417□□□□□□□□TLC-39□□□□□□□□MAXICODE□□QR□□MicroQR□□□□□□□□
□□	USB
□□□□	□□□□1□□□□□□□□□□□□300m□□□□□□□□
□□□□	-10□□□□ - 45□□□□
□□□□	-20□□□□ - 65□□□□
□□□□	5□-85□
□□□□	5□-95□
□□□□	□□□□□□□□1.8□□□□□□□□□□□□
□□□□	DC 5V□□350mA
Lumination	□□□□3.000 LUX□□□□;□□□□□□□□86000LUX□□□□
EMC	EN50081□□PAR1□□□□
FCC	EN50082□□PAR1□□□□
IP□□	IP42
□□□□	
□□□□*	
□□□□□□□□	
HD□□□□□□	
□□□□	□□□□
39□	5.0□
100□UPCA	13.0□
39□	20.0□
PDF 417	6.8□
□□□□	10.0□
□□□□	20.0□
□□□□1D□39	2.8□□□□0.071□□□□
□□□□□□□□□□	4.8□□□□0.122□□□□
□□	ABS + PC
□□	95x65x155mm
□□	160□
□□□□□□	18.2X11.7X11.2cm
□□□□□□	374□

