

□□□□□□2D□□□□□□□□□□

□□□□□□-W230□

□□□

| | | | |
|------------|--|------|-------|
| □□□□ | 617□□LED | | |
| □□□□ | 625□□LED | | |
| □□□□ | 39°□H□×25°□V□ | | |
| □□□□ | 0 - 360° | | |
| □□ | ±65° | | |
| □□ | ±60° | | |
| □□□□□□ | □□25□ | | |
| 1D | UPC / EAN□□UPC / EAN□□□□□□BooklandEAN□□ISSN□□UCC□□□□□□□□□□Code128□□GS1-128□□ISBT 128 □□39□□39□□ASCII□□Trioptic 39□□32□□93□□Code11□□□□□□2 5□□□2 5□□□2of 5□□□□□□□□□□5□□2□□GS1 □□Barvariants□□□3 5□□□□□□□□Concat□ | | |
| 2D | PDF417□□MicroPDF417□□□□□□□□TLC-39□□□□□□□□MAXICODE□□QR□□MicroQR□□□□□□□□ | | |
| □□ | USB | | |
| □□□□ | □□□□1□□□□□□□□□□□□300m□□□□□□□□ | | |
| □□□□ | -10□□□□ - 45□□□□ | | |
| □□□□ | -20□□□□ - 65□□□□ | | |
| □□□□ | 5□-85□ | | |
| □□□□ | 5□-95□ | | |
| □□□□ | □□□□□□□□1.8□□□□□□□□□□□□ | | |
| □□□□ | DC 5V□□350mA | | |
| Lumination | □□□□3.000 LUX□□□□;□□□□□□□□86000LUX□□□□ | | |
| EMC | EN50081□□PAR1□□□□ | | |
| FCC | EN50082□□PAR1□□□□ | | |
| IP□□ | IP42 | | |
| □□□□ | | | |
| □□□□* | □□□□□□□□□□ | | |
| | HD□□□□□□ | | |
| □□□□ | □□□□ | | |
| 39□ | 5.0□ | 5□□ | 90□□ |
| 100□□UPCA | 13.0□ | 8□□ | 200□□ |
| 39□ | 20.0□ | 8□□ | 250□□ |
| PDF 417 | 6.8□ | 5□□ | 95□□ |
| □□□□ | 10.0□ | 5□□ | 110□□ |
| □□□□ | 20.0□ | 10□□ | 150□□ |
| □□□□1D□□39 | 2.8□□□□0.071□□□□ | | |
| □□□□□□□□□□ | 4.8□□□□0.122□□□□ | | |
| □□ | ABS + PC | | |
| □□ | 95x65x155mm | | |
| □□ | 160□ | | |
| □□□□□□ | 18.2X11.7X11.2cm | | |
| □□□□□□ | 374□ | | |

