

USB
OCBS-LA06

OCBS-LA06

| | |
|-----------|--|
| OCBS-LA06 | |
| OCBS-LA06 | 650-670nm |
| OCBS-LA06 | 100 |
| OCBS-LA06 | 2.5 600 100 UPC / EAN |
| OCBS-LA06 | |
| OCBS-LA06 | 0.10 4MIL PCS 0.9 |
| OCBS-LA06 | 20%, @ 650nm |
| OCBS-LA06 | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| OCBS-LA06 | |
| OCBS-LA06 | PS2 RS232 USB |
| OCBS-LA06 | DC + 5V +/- 5 |
| OCBS-LA06 | 100 |
| OCBS-LA06 | <40 |
| OCBS-LA06 | RS232 |
| OCBS-LA06 | 45° 60° |
| OCBS-LA06 | L165.42mm xW69.72mm xH89.67mm |
| OCBS-LA06 | 140 |
| OCBS-LA06 | |
| OCBS-LA06 | |
| OCBS-LA06 | |
| OCBS-LA06 | 0 ~50 degree eC |
| OCBS-LA06 | -40~70degreeç |
| OCBS-LA06 | 5~95 |
| OCBS-LA06 | ±15kV +8KV |
| OCBS-LA06 | 1.5 |
| OCBS-LA06 | |
| EMI / RFI | FCC A CE |
| OCBS-LA06 | CDRH 2 |

OCBS-LA06

