

# OCBS 1D / 2D

## OCBS -2018

### Feautre

OCBS

1MP 1MP 1280 \* 800;

OCBS

OCBS 1D 2D

OCBS

4mil

OCBS

OCBS

OCBS	USB; RS232
OCBS	Linux Android Windows XP 7 8 10 MAC
OCBS	OCBS; OCBS; OCBS; OCBS
OCBS	OCBS CMOS
OCBS	OCBS LED + OCBS LED
OCBS	32 ARM MCU + DSP
OCBS	Code39 35cm /
OCBS	400
OCBS	1/5
OCBS	OCBS
OCBS	OCBS
OCBS	OCBS LED
OCBS	20
OCBS	ABS +
OCBS	OCBS 5V ± 5
OCBS	375mW; 226mW; 750mW
OCBS	OCBS
OCBS	145.0g ± 5g
OCBS	OCBS * OCBS 164.5 * 91.5 * 68.0 mm
OCBS	OCBS +

□□□□	□□	●□□25□□●□□25□□-□□25□□
		●□□39-□□●□□39-□ASCII●□□32
		●□□93-□□●□□93-□ASCII●□□128
		●EAN / GSL / UCC-128Auto●Codabar●MSI
		●EAN / JAN-13●UPC-A●JAN-8●Code11●UPCE0
	2D	●MICRO QR●□□□□●QR ●AZTEC●PDF417
□□□□	□□360°□□□30°□□□45°	
□□□□	Code39 4.17mil□15□□□□6cm-12cm	
	Code128 4.17mil□16□□□□7cm-10cm	
	□□□□10.83mil□8 bytes□□5cm-16cm	
	□QR 1083mil□8 bytes□□7cm-12cm	
□□□□		
IP□□	IP52	
□□□□	0□50°C/ 32□122°F	
□□□□	0□50°C/ 32□122°F	
□□□□	20□□85□□□□□□□□	
□□□□	20□□85□□□□□□□□	
□□□□	15KV□□	
□□□□	□□□□□□□□1.5m	



OCBS-2018





OCBS-2018





