

Android

M/N OCBS -D5000

Android 7.0

2G RAM+16G ROM

5.0 720*1280 Gorilla HD

IP65/1.5M

3.7V 4500mAh

8 MP LED

HHW

1D/2D

LRFID LF/HF/UHF/NFC

TCS15M

	170mmh x 85mmw x 23mmd ± 2 mm
	380
	Gorilla 5.0 TFT-LCD 720x1280
	LED
	3TP 6 4
	2 psam 1 SIM 1 TF
	3.7V 4500mAh UHF 8000mAh
	Quad A53 1.5GHz
	Android 7.0
	2GB RAM 16GB ROM microSD 32GB
	-20°C 50°C
	-20°C 70°C
	5rh 95RH
	5ft./1.5 m
	IP65 IEC
ESD	±15kV ±8kV ±8kV

SDK	HHW
	Android Studio/Eclipse
WWAN	TDD-LTE 38/39/40 FDD-LTE 1,2,3,4,7; WCDMA 850/1900/2100MHz; GSM/GPRS/EDGE 850/900/1800/1900MHz;
wlan	2.4G/5G IEEE 802.11 A/B/G/N/AC
WPAN	v2.1+EDR v3.0+HS v4.0
	GPS A-GP 5 m
1D	1D Honeywell N431X 1D
2D	2D CMOS Honeywell N6603 Symbologies PDF417/MicroPDF417/COM pos ITE/RSS/TLC-39/DATAMATRIX/QR/Micro QR/Aztec/ Aztec/Maxicode/Pos TAL/US Pos TNET/US Pos TNET/UK Pos TAL/UK Pos TAL/ukPos tal/uk Pos tal/uka Pos tal/uka Pos tal/Australaian Pos tal/ TAL/ Pos TAL
	8.0
	LED
RFID	
RFID LF	125kHz/134.2kHz FDX-B/HDX ISO 11784/11785 R/W 2/10
RFID HF	13.56MHz ISO 14443A/15693 R/W 2/8
RFID UHF	865/868MHz/920/925MHz EPC C1 GEN2/ISO 18000-6C 2DBI R/W 1 m/1.5 m
2.45GHz	200 m
433MHz	200 m
Zigbee	
	IEEE 802.15.4
	100 m/200 m
	TCS15M
	508 DPI
	FRR<0.008%, FAR<0.005%
	1000
PSAM	
	ISO 7816

□□□	9600□19200□38400,43000□56000□57600□115200
□□□	2□□□□□□□□□□
□□	
□□	1x□□□□□ 1xlithium□□□□□□ 1XDC□□□□□ 1XUSB□□□□□
□□□	□□□□□□UHF□□□□

□□□□













