

□□□□□□□□□□□□□□□□

□□□□□□-W230□

□□□

□□□□	617□□LED
□□□□	625□□LED
□□□□	39°□H□×25°□V□
□□□□	0 - 360°
□□	±65°
□□	±60°
□□□□□□	□□25□
1D	UPC / EAN□□UPC / EAN□□□□BooklandEAN□ISSN□UCC□□□□□□□□Code128□GS1-128□ISBT 128 □□39□□39□□ASCII□□Trioptic 39□□32□□93□□Code11□□□□□2 5□□□2 5□□□2of 5□□□□□□□□5□□2□GS1 □□Barvariants□□□3 5□□□□□□□Concat□
2D	PDF417□MicroPDF417□□□□□□TLC-39□□□□□□MAXICODE□QR□□MicroQR□□□□□□
□□	USB
□□□□	□□□1□□□□□□□□□300m□□□□□□
□□□□	-10□□□ - 45□□□
□□□□	-20□□□ - 65□□□
□□□□	5□-85□
□□□□	5□-95□
□□□	□□□□□1.8□□□□□□□□□
□□□□	DC 5V□350mA
Lumination	□□□3.000 LUX□□;□□□□□□□86000LUX□□
EMC	EN50081□PAR1□□
FCC	EN50082□PAR1□□
IP□□	IP42
□□□□	
□□□□*	□□□□□□□□
	HD□□□□□
□□□□	□□□□□
39□	5.0□
100□UPCA	13.0□
39□	20.0□
PDF 417	6.8□
□□□□	10.0□
□□□	20.0□
□□□1D□39	2.8□□□0.071□□□
□□□□□□□□□	4.8□□□0.122□□□
□□	ABS + PC
□□	95x65x155mm
□□	160□
□□□□□	18.2X11.7X11.2cm
□□□□□	374□

