

OCBS -W600

OCBS

OCBS	
OCBS	OCBS VLD @ 650 nm-670nm
OCBS	164mm * 67mm * 95mm W * H * D
OCBS	130mm*45mm*129mm W * H * D
OCBS	ABS + TPR /OCBS
OCBS	235
OCBS	OCBS:OCBS
OCBS	LED OCBS
OCBS	OCBS
OCBS	
OCBS	60mm@30mm 98mm@100mm
OCBS	2.5-600mm 0.9mm 0.25mm
OCBS	OCBS 100mm
OCBS	0.10mm 4MIL PCS0.9
OCBS	1 / 500mm
OCBS	UPC / EAN / UCC / EAN128 / Code 39 / Code 39 ASCII / Trioptic Code 39 / Code 128 / Code 128 Full ASCII / Codabar / Interleaved 2 of 5 / Discrete 2 of 5 / Code 93 / MSI / RSS / 2 of 5
OCBS	3.7V / 750mAh
OCBS	3.0mm
OCBS	30mm
OCBS	100mA; 40mm
OCBS	OCBS 60°; OCBS 45°
OCBS	30mm
OCBS	2.4G
OCBS	USB
OCBS	
OCBS	OCBS. OCBS. OCBS -40OCBS. 70 OCBS. OCBS
OCBS	5-90mm
OCBS	OCBS 1.5mm
OCBS	0~100,000 LUX
OCBS	OCBS ±12KV OCBS ±6KV
OCBS	CE FCC Class 2 RoHS

OCBS



Wireless Barcode Scanner

OCBS-W600



Product Picture





Features

Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100scans/sec



Scan speed: 1000/second

Data transmission distance reaches
30m in open area;



Scan Time: 30hours





||| All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	2.5-600mm (Contrast 0.9 Density 0.25)
Scan Speed	100 scans/sec
Scan Precision	0.10mm (4mil) PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB ,RS232,PS2
USER ENVIRONMENT CHARACTERSTICS	
Temperature	0°C to 50°C (Operating), -40°C to 70°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



Moneybookers Visa MasterCard

5.

6.

Eruopean ...