

15.6吋Windows/Android雙系統 POS 電腦

(M/N POS-1562)

OCOM POS-1562 POS 電腦採用Intel Celeron雙系統CPU，I/O埠齊全，

雙系統



雙系統 POS 電腦

雙系統

雙系統

|                  |                                               |                                      |
|------------------|-----------------------------------------------|--------------------------------------|
|                  | POS-1562-W                                    | POS-1562-A                           |
|                  | 15.6  POS                                     |                                      |
|                  |                                               |                                      |
|                  |                                               |                                      |
|                  | 15.6                                          |                                      |
|                  | 1366*768                                      |                                      |
|                  | 220cd/                                        |                                      |
|                  | 90 60                                         |                                      |
|                  | GG                                            |                                      |
|                  | 11.6                                          |                                      |
|                  |                                               |                                      |
|                  | Intel Celeron J6412, 2.0GHz Intel core I3 CPU | Rockchip RK3568 2.0G                 |
|                  | 1*SO-DIMM DDR4 3200mHZ 4GB /8GB /16G          | DDR4 4GB 8G                          |
|                  | 64GB M.2 SSD  512GB                           | 32GB EMMC 64GB                       |
| /                | 10/100/1000Mbps,Realtek RTL8111F              | 10/100/1000Mbps,Realtek RTL8111F LAN |
|                  | Mini PCI-E WIFI                               | Wi-Fi 802.11a/b/g/n, BT3.0/BT4.0     |
|                  | Windows 10/11                                 | 11                                   |
|                  |                                               |                                      |
| <br>I/O<br>J6412 | *1                                            |                                      |
|                  | 12V DC  *1                                    |                                      |
|                  | RJ-45*1 USB*6 COM*2 HDMI*1                    |                                      |
|                  | 2  1  *1                                      |                                      |

|               |                               |
|---------------|-------------------------------|
| I/O<br>RK3568 | GPIO*1                        |
|               | 12V DC GPIO*1                 |
|               | GPIORJ-45*1GPIOUSB*6GPIOCOM*1 |
|               | GPIO*1                        |
|               |                               |
|               | 0~50%                         |
|               | -20~60%                       |
|               | 10%~90%                       |
|               | 10%~90%                       |
|               |                               |
|               | 3.6kg~4.9kg                   |
|               | 430*240*370mm                 |
|               |                               |
|               | 110-240V/50-60HZ  DC12V/5A    |
|               | / /                           |







