

Feautre[]

000001D02D00000000

5mil______

ППП

Standard 2 of 5[Telepen[TLC 39]] 1D			
LED 617 ±10			
			640 * 480[256[[
			LED[]617[][]±10[][]
			0[100,000][[
			\[\]360°\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Standard 2 of 5[Telepen[TLC 39]] 1D			300scan /[
EAN128		2D	DataMatrix Matrix 2 of 5 MaxiCode MicroPDF417 MSI Code PDF417 QR code Standard 2 of 5 Telepen TLC 39
□ ≥5mil□□□□□□ □ 360° □ 75° □□□ RS232 / USB / USB□□COM □ □ □ 190 mA□□□□ □ 1.5□ □ 165□ □ 170□x 60□x95□□ □ -5°C□65°C □ -20°C□70°C □ 5□-95□□□□□		1D	
65° 75°			
75°			360°
RS232 / USB / USB COM			65°
RS232 / USB / USB COM			75°
□ 190 mA□□□□ □ 1.5□ □ 165□ □ 170□x 60□x95□□ □ -5°C□65°C □ -20°C□70°C □ 5□-95□□□□□□			RS232 / USB / USB□□COM
1.5 165 170 170 170 170 170 170 170 170 170 170 170 170 180 1			□□5 V±5□
[] [] []			190 mA[[[[[]]
170 x 60 x95 			1.5[
0000 000 -5°C[65°C 000 -20°C[70°C 0 5[-95]0000			165[]
-5°C 65°C			170x 60x95
00 50-9500000			-5°C∏65°C
			-20°C∏70°C
			50-9500000
			01500000000









1.00000

2.

3.[[

4. []]]]
5. 00 000000000000000000000000000000
6.□□
Eruopean
0000133000/0001300000000000000000000000

##