## \_\_\_usb 2d\_\_\_\_

### \_\_\_\_ OCBS -2008

4mil;
ППППП

		[][]LED			
		<u></u>			
		CMOS			
		640 * 480,256∏			
		13mil UPC 40cm / s			
		00500:00200			
ПП		≥4mil			
0000	1D	UPC-A\underlightarrow UPC-E\underlightarrow UPC-A\underlightarrow UPC-E\underlightarrow			
	2D	PDF417[MicroPDF417[]QR Code[]DataMatrix[]Han Xin Code[]Aztec Code[]GS1 Com posite			
		39  5mil   50mm~120mm    39  10mil   25mm~250mm   UPC / EAN  13mil   20mm~320mm      0    7.5mil   63mm~150mm   DD  166mil   62  145			
		±45°@ 0°Roll  0°Skew   ±30°@ 0°  0°  0°  0°  0°  0°  0°  0°  0°  0°			
		USB[]USB COM[][][][]			
		3.3v~5v DC			
		2.0w[400mA[			
		2.5w[450mA[			
		□□5.5V 1A			
LED CLASS					
EMC[]		FCC[]15[][][IEC60825-1[]EN55022 B[]			
		-20+ 604144			
		-30+ 7022158			
		50 - 9500000			
		1.5005.000000000			
IP[]		IP54			
		00000000			
		•			
		156 * 68 *83∏			
		195			
		48 * 36 * 47CM[20[[[]]]13.5KG[]			
		48 * 39 * 52CM[]30[][][]15KG[]			



# Product Picture



### Features

### Reliable with good price

High performance imaging technology; Omni-directional scanning, easy to scan;





Multi special function setting supported; SDK/API Available;



Multi interfaces optional; Stand for option.




### Application place



Bookstore



Supermakte



Pharmacy



Warehouse



Clothing store



Restaurant

# Parameter

Function					
Light source		White LED			
Веер		Supported			
Stand		Optional			
Indicator		Green LED, beep			
Scan performance					
Sensor	100	CMOS			
Resolution	6,,	640*480,256 gray levels			
Maximum decoding s	peed	13mil UPC 40cm/s			
Reading angle		horizontally 50 deg; vertically 20 Deg			
Precision		≥4mil			
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Cod 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-13) ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey			
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite			
Depth of field  Sensitivity		Code 39(5mil): 50mm~120mm  Code 39(10mil): 25mm~250mm  UPC/EAN (13mil): 20mm~320mm  Data Matrix(7.5mil): 63mm~150mm  PDF417(6.6mil): 62mm~145mm			
		Inclination ±45° @0°Roll and 0°Skew  Rotation ±30° @0°Pitch and 0°Skew  Deflection ±45° @0°Roll and 0°Skew			
Electrical					
Interface		USB,USB COM(virtual serial port)			
Input Voltage		3.3v~5v DC			
Standard Power		2.0w (400mA)			
Max Power		2.5w (450mA)			
DC adapter	AR.	Max 5.5V 1A			
LED CLASS	0	Class I			
EMC Test		FCC part15,IEC60825-1,EN55022 Class B			
User Environment					
Operate Temperature		-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)			
Storage Temperature		-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)			
Humidity		5% - 95%(non- condensation)			
Drop resistance:		1.5m (5.0ft) drops to concrete			
IP class		IP54			
Light intensity		Working: sun lights, fluorescent lights			
Physical					
Dimensions		156*68*83mm			
Weight		195 g (without stand)			
Package dimension		48*36*47CM (20pcs with stand 13.5KG)			



#### ✓ Indicates information has been verified onsite by a certification specialist. **Production Capacity** Verified Product Name Production Line Capacity Actual Units Produced(Previous Year) Thermal Printer 40,000 Sets / Month 250,000 Sets Dot Matrix Printer 15,000 Sets / Month 10,000 Sets Bluetooth Printer 30,000 Sets / Month 20 000 Sets Barcode Scanner 40,000 Sets / Month 20,000 Sets POS Machine 5,000 Sets / Month 10,000 Sets Magnetic Card Reader and Writer 45,000 Sets / Month 50,000 Sets

Verified by TUV on 2013.7.15

#### Quality Assurance:



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers's atisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

#### Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist.

#### Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
1	Ageing Tester	No Information	6
1	Withstand Voltage Tester	CC2670A	1
V	Oscilloscope	TBS1102	1
V	DC Power Supply	PS-305DM	6
1	Digital Torque Meter	HP100	1
1	Calliper	GUANGLU	2
1	Multi-meter	VC890D	7
V	Test Computer	No Information	13

Verified by TUV on 2013.7.15

#### Certification:










#### Warranty and After Sales:



- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7\*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

#### Packing and Shipment:





#### Payment:









secure payment







Trade Assurance

#### Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.



### Company Profile





OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers, Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs. OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.













1 OCOM24
2.
<b>3.</b>
4&
5.0000 *000000010000000000000000000000000
6.[[] [[][][http[]// www[] pos solution.com.cn/cn/download.html
7
<b>8.</b>